



## Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-6378-5	<b>Version number:</b>	5.00
<b>Revision date:</b>	27/11/2014	<b>Supersedes date:</b>	26/06/2013
<b>Transportation version number:</b>	4.00 (09/06/2012)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotchkote Intumescent Sealer LS4000 CL, Satin

#### Product Identification Numbers

GR-2000-9973-1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Coating.

#### 1.3. Details of the supplier of the substance or mixture

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Flammable Liquid, Category 3 - Flam. Liq. 3; H226  
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

**Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive**

**Indication of danger**

## 3M Scotchkote Intumescent Sealer LS4000 CL, Satin

Flammable; R10  
Irritant; Xi; R38  
Harmful; Xn; R48/20  
Dangerous for the environment; N; R51/53

For full text of R phrases, see Section 16.

### 2.2. Label elements

#### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER!

#### Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

#### Pictograms



Ingredient	CAS Nbr	% by Wt
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	40 - 50

#### HAZARD STATEMENTS:

H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H372	Causes damage to organs through prolonged or repeated exposure: nervous system
H411	Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260E	Do not breathe vapour or spray.
P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.

##### Response:

P331	Do NOT induce vomiting.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

##### Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

#### SUPPLEMENTAL INFORMATION

##### Supplemental Hazard Statements:

### 3M Scotchkote Intumescent Sealer LS4000 CL, Satin

EUH208 Contains 2-Butanone oxime. | cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

49% of the mixture consists of components of unknown acute inhalation toxicity.  
Contains 4% of components with unknown hazards to the aquatic environment.

#### Notes on labelling

H304 is not required on the label due to the product's viscosity  
Nota P applied to CASRNs 64742-82-1 and 64742-48-9.

#### Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

##### Symbol(s)



Harmful



Irritant



Dangerous  
for the  
environment

##### Contains:

Naphtha (petroleum), hydrodesulphurised heavy

##### Risk phrases

R10 Flammable.  
R38 Irritating to skin.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

##### Safety phrases

S23C Do not breathe vapour or spray.  
S51 Use only in well ventilated areas.  
S24 Avoid contact with skin.  
S62 If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label.  
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

##### Special provisions concerning the labelling of certain substances

Contains 2- Butanone oxime Contains Cobalt Octoate May produce an allergic reaction.

##### Notes on labelling

R65 is not required on the label due to the product's viscosity.

Nota P applied to CASRNs 64742-82-1 and 64742-48-9.

#### 2.3. Other hazards

None known.

### SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Non-hazardous ingredients	Mixture		40 - 50	
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	EINECS 265-185-4	40 - 50	Xn:R48/20; Xn:R65 - Nota P (EU)

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

				F:R11; Xi:R38; N:R51/53 (Self Classified)  Asp. Tox. 1, H304; STOT RE 1, H372 - Nota P (CLP) Flam. Liq. 2, H225; Skin Irrit. 2, H315; Aquatic Chronic 2, H411 (Self Classified)
Synthetic amorphous silica, fumed, crystalline free	112945-52-5		1 - 5	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EINECS 265-150-3	1 - 5	Xn:R65 - Nota 4,P (EU) Xi:R38; R67 (Self Classified)  Asp. Tox. 1, H304 - Nota P (CLP) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
1,2,4-Trimethylbenzene	95-63-6	EINECS 202-436-9	< 2	Xn:R20; Xi:R36-37-38; N:R51/53; R10 (EU)  Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 2, H411 (CLP)
2-Butanone oxime	96-29-7	EINECS 202-496-6	< 1	Carc. Cat. 3:R40; Xn:R21; Xi:R41; R43 (EU) R52/53 (Self Classified)  Acute Tox. 4, H312; Eye Dam. 1, H318; Skin Sens. 1, H317; Carc. 2, H351 (CLP)
cobalt bis(2-ethylhexanoate)	136-52-7	EINECS 205-250-6	< 1	Xi:R38; R43 (Vendor) N:R51/53 (Self Classified)  Skin Irrit. 2, H315; Skin Sens. 1, H317 (Vendor) Aquatic Chronic 2, H411 (Self Classified)

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

## 3M Scotchkote Intumescent Sealer LS4000 CL, Satin

### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning: A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	112945-52-5	UK HSC	TWA(as inhalable dust):6 mg/m <sup>3</sup> ;TWA(as respirable dust):2.4 mg/m <sup>3</sup>	
Cobalt compounds	136-52-7	UK HSC	TWA(as Co):0.1 mg/m <sup>3</sup>	Respiratory Sensitizer
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Manufacturer determined	TWA:100 ppm	
Benzene, trimethyl-	95-63-6	UK HSC	TWA:125 mg/m <sup>3</sup> (25 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

### 3M Scotchkote Intumescent Sealer LS4000 CL, Satin

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polyvinyl alcohol (PVA).	No data available	No data available
Polymer laminate	No data available	No data available

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Aromatic solvent odour; Clear colour
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	$\geq 145$ °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	38 °C [ <i>Test Method</i> :Closed Cup]
Autoignition temperature	$\geq 240$ °C
Flammable Limits(LEL)	0.9 % volume
Flammable Limits(UEL)	8 % volume
Vapour pressure	586.6 Pa [ <i>@ 25 °C</i> ]
Relative density	0.90 [ <i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	0.2 Pa-s
Density	0.9 g/ml

### 9.2. Other information

Volatile organic compounds (VOC)	463 g/l [ <i>Test Method</i> :Estimated] [ <i>Details</i> :EU Definition]
Percent volatile	51.41 % weight

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

Temperatures above the boiling point.

### 10.5 Incompatible materials

Alcohols.

Combustibles.

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Strong acids.

Strong bases.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

#### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.



**3M Scotchkote Intumescent Sealer LS4000 CL, Satin****Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Target Organ Effects:****Single exposure may cause:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrodesulphurised heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrodesulphurised heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Rat	LD50 > 5,110 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg
2-Butanone oxime	Dermal	Rabbit	LD50 > 1,000 mg/kg
2-Butanone oxime	Inhalation-Vapor	Rat	LC50 estimated to be 20 - 50 mg/l
2-Butanone oxime	Ingestion	Rat	LD50 2,300 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Naphtha (petroleum), hydrodesulphurised heavy	Rabbit	Irritant
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
1,2,4-Trimethylbenzene	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Naphtha (petroleum), hydrodesulphurised heavy	Rabbit	No significant irritation
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
1,2,4-Trimethylbenzene	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
Naphtha (petroleum), hydrodesulphurised heavy	Guinea pig	Not sensitizing
Naphtha (petroleum), hydrotreated heavy	Guinea pig	Not sensitizing

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

Synthetic amorphous silica, fumed, crystalline free	Human and animal	Not sensitizing
1,2,4-Trimethylbenzene	Guinea pig	Not sensitizing

**Respiratory Sensitisation**

Name	Species	Value
------	---------	-------

**Germ Cell Mutagenicity**

Name	Route	Value
Naphtha (petroleum), hydrodesulphurised heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrodesulphurised heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	In Vitro	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Naphtha (petroleum), hydrodesulphurised heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
1,2,4-Trimethylbenzene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.5 mg/l	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

						<b>Duration</b>
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

<b>Name</b>	<b>Route</b>	<b>Target Organ(s)</b>	<b>Value</b>	<b>Species</b>	<b>Test result</b>	<b>Exposure Duration</b>
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrodesulphurised heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Synthetic amorphous silica, fumed, crystalline free	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	heart   endocrine system   immune system	All data are negative	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver   immune system   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

Name	Value
Naphtha (petroleum), hydrodesulphurised heavy	Aspiration hazard
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Non-hazardous ingredients	Mixture		Data not available or insufficient for classification			
2-Butanone oxime	96-29-7	Water flea	Experimental	21 days	NOEC	>100 mg/l
2-Butanone oxime	96-29-7	Green algae	Experimental	72 hours	NOEC	2.6 mg/l
2-Butanone oxime	96-29-7	Water flea	Experimental	48 hours	EC50	200 mg/l
2-Butanone oxime	96-29-7	Green algae	Experimental	72 hours	EC50	16 mg/l
1,2,4-Trimethylbenzene	95-63-6	Fathead minnow	Experimental	96 hours	LC50	7.72 mg/l
1,2,4-Trimethylbenzene	95-63-6	Mysid Shrimp	Experimental	96 hours	EC50	2 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Experimental	48 hours	EC50	3.6 mg/l

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	Crustacea	Experimental	96 hours	EC50	2.6 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green Algae	Experimental	72 hours	NOEC	60 mg/l
cobalt bis(2-ethylhexanoate)	136-52-7	Rainbow trout	Estimated	96 hours	LC50	3.75 mg/l
cobalt bis(2-ethylhexanoate)	136-52-7	Water flea	Estimated	48 hours	EC50	2.95 mg/l
cobalt bis(2-ethylhexanoate)	136-52-7	Green algae	Estimated	96 hours	EC50	1.38 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	Estimated Photolysis		Photolytic half-life (in air)	12.99 days (t 1/2)	Other methods
1,2,4-Trimethylbenzene	95-63-6	Experimental Photolysis		Photolytic half-life (in air)	11.8 hours (t 1/2)	Other methods
Non-hazardous ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Butanone oxime	96-29-7	Experimental Hydrolysis		Hydrolytic half-life	18 days (t 1/2)	Other methods
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha	64742-48-9	Data not	N/A	N/A	N/A	N/A

**3M Scotchkote Intumescent Sealer LS4000 CL, Satin**

(petroleum), hydrotreated heavy		available or insufficient for classification				
1,2,4-Trimethylbenzene	95-63-6	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301C - MITI test (I)
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	Experimental Biodegradation	28 days	BOD	75 % weight	OECD 301F - Manometric respirometry
cobalt bis(2-ethylhexanoate)	136-52-7	Experimental Biodegradation	28 days	BOD	39 % weight	Other methods

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-hazardous ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
cobalt bis(2-ethylhexanoate)	136-52-7	Estimated BCF - Fathead Mi	63 days	Bioaccumulation factor	190	Other methods
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Butanone oxime	96-29-7	Experimental BCF - Other	42 days	Bioaccumulation factor	<5.8	OECD 305C-Bioaccum degree fish
1,2,4-Trimethylbenzene	95-63-6	Experimental BCF-Carp	56 days	Bioaccumulation factor	275	Other methods
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	Experimental Bioconcentration		Bioaccumulation factor	>1000	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

No information available at this time, contact manufacturer for more details

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

## 3M Scotchkote Intumescent Sealer LS4000 CL, Satin

### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transportation information

GR-2000-9973-1

**ADR/RID:** UN1263, PAINT RELATED MATERIAL, LIMITED QUANTITY, 3., III, (E), ADR Classification Code: F1.

**IMDG-CODE:** UN1263, PAINT RELATED MATERIAL, 3, III, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FE,SE.

**ICAO/IATA:** UN1263, PAINT RELATED MATERIAL, 3., III.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2-Butanone oxime	96-29-7	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
2-Butanone oxime	96-29-7	Carc.Cat.3	Regulation (EC) No. 1272/2008, Table 3.2

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**List of relevant R-phrases**

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R21	Harmful in contact with skin.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R65	Harmful: May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

**Revision information:**

Revision Changes:

Section 8: Eye/face protection information information was modified.

Risk phrase information was modified.

Section 1: Product identification numbers heading information was modified.

Section 9: Viscosity information information was modified.

Section 16: List of relevant R phrase information information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 2: Indication of danger information information was modified.

Section 2: EU sensitizer phrase information was modified.

Section 15: Regulations - Inventories information was modified.

Copyright information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Telephone header information was modified.

Company Telephone information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.



Section 11: Skin Sensitization Table information was modified.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Skin Corrosion/Irritation Table information was modified.  
Section 11: Target Organs - Repeated Table information was modified.  
Section 11: Target Organs - Single Table information was modified.  
Section 11: Health Effects - Skin information information was modified.  
Section 11: Health Effects - Inhalation information information was modified.  
Section 5: Fire - Extinguishing media information information was modified.  
Section 6: Accidental release clean-up information information was modified.  
Section 7: Precautions safe handling information information was modified.  
Section 7: Conditions safe storage information was modified.  
Section 8: Personal Protection - Eye information information was modified.  
Section 13: 13.1. Waste disposal note information was modified.  
Section 13: Standard Phrase Category Waste GHS information was modified.  
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.  
Label: Graphic Text information was modified.  
Label: Graphic information was modified.  
Label: Graphic Text information was modified.  
Section 2: Label ingredient information information was added.  
Section 12: Component ecotoxicity information information was added.  
Section 12: Persistence and Degradability information information was added.  
Section 12:Biocumulative potential information information was added.  
Section 12: Component Ecotoxicity table Material column header information was added.  
Section 12: Component Ecotoxicity table CAS No column header information was added.  
Section 12: Component Ecotoxicity table Organism column header information was added.  
Section 12: Component Ecotoxicity table Type column header information was added.  
Section 12: Component Ecotoxicity table Exposure column header information was added.  
Section 12: Component Ecotoxicity table End point column header information was added.  
Section 12: Component Ecotoxicity table Result column header information was added.  
Section 12: Persistence and degradability table Material column header information was added.  
Section 12: Persistence and degradability table CAS No column header information was added.  
Section 12: Persistence and degradability table Test Type column header information was added.  
Section 12: Persistence and degradability table Duration column header information was added.  
Section 12: Persistence and degradability table Test Result column header information was added.  
Section 12: Persistence and degradability table Protocol column header information was added.  
Section 12:Biocumulative potential table Material column header information was added.  
Section 12:Biocumulative potential table CAS No column header information was added.  
Section 12:Biocumulative potential table CAS No column header information was added.  
Section 12:Biocumulative potential table Test Result column header information was added.  
Section 12:Biocumulative potential table Protocol column header information was added.  
Section 12:Biocumulative potential table Test Type column header information was added.  
Label: Signal Word - Header information was added.  
Label: Signal Word information was added.  
Label: CLP Classification - Header information was added.  
Label: CLP Classification information was added.  
Label: CLP Classification information was added.  
Label: CLP Classification - Header information was added.  
Label: CLP Percent Unknown information was added.  
Label: CLP Percent Unknown information was added.  
Label: CLP Environmental Hazard Statements information was added.  
Label: Graphic information was added.  
Label: Graphic information was added.  
Label: Symbol information was added.  
Label: Symbol information was added.  
Label: CLP Precautionary - Disposal information was added.

Label: CLP Precautionary - Disposal - Header information was added.  
Label: CLP Precautionary - Prevention information was added.  
Label: CLP Precautionary - Prevention - Header information was added.  
Label: CLP Precautionary - Response information was added.  
Label: CLP Precautionary - Response - Header information was added.  
Label: Precautionary Statement - Header information was added.  
CLP: Ingredient table information was added.  
Label: CLP Supplemental Hazard Statements - Header information was added.  
Label: CLP Supplemental Information - Header information was added.  
Contains statement for sensitizers information was added.  
Contains statement for sensitizers information was added.  
Contains statement for sensitizers information was added.  
Section 2: Notes on labelling heading information was added.  
Section 15: Label remarks and EU Detergent information was added.  
Section 8: Occupational exposure limit table information was added.  
CLP Remark(phrase) information was added.  
Section 2: 2.2 & 2.3. CLP REGULATION heading information was added.  
Section 8: Personal Protection - Skin/hand information information was added.  
Section 8: Personal Protection - Respiratory Information information was added.  
Label: CLP Ingredients table Ingredient heading information was added.  
Label: CLP Ingredients table CAS No heading information was added.  
Label: CLP Ingredients table Percent by Wt heading information was added.  
Section 12: Persistence and degradability table Study Type column header information was added.  
Section 12: Biocumulative potential table Test Type column header information was added.  
Label: Graphic Text information was added.  
Section 2: H phrase reference information was added.  
Section 10: Hazardous decomposition products during combustion text information was added.  
Label: CLP Target Organ Hazard Statement Heading information was added.  
Label: CLP Target Organ Hazard Statement information was added.  
Section 11: Disclosed components not in tables text information was added.  
Section 12: Classification Warning information was added.  
Section 11: Classification disclaimer information was added.  
Section 8: 8.1.1 Biological limit values table heading information was added.  
Section 8: BLV information was added.  
List of sensitizers information was added.  
Section 8: glove data - Material heading information was added.  
Section 8: glove data - Thickness heading information was added.  
Section 8: glove data - Breakthrough Time heading information was added.  
Section 8: glove data value information was added.  
Section 8: Skin protection - recommended gloves information information was deleted.  
Section 8: Eye/face protection text information was deleted.  
Section 8: Personal Protection - Skin/body information information was deleted.  
Section 8: Respiratory protection - recommended respirators information was deleted.  
Section 8: Skin protection - protective clothing information information was deleted.  
Section 8: Skin protection - protective clothing text information was deleted.  
Section 2: Label ingredient information information was deleted.  
Prints No Data if Component ecotoxicity information is not present information was deleted.  
Prints No Data if Persistence and Degradability information is not present information was deleted.  
Prints No Data if Biocumulative potential information is not present information was deleted.  
Section 8: mg/m<sup>3</sup> key information was deleted.  
Section 8: ppm key information was deleted.  
Section 11: Classification disclaimer information was deleted.  
Section 11: Respiratory Sensitization Table information was deleted.  
Section 12: Classification Warning information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

<b>3M Scotchkote Intumescent Sealer LS4000 CL, Satin</b>
--

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)**