



Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-1688-0	Version number:	2.00
Revision date:	17/09/2013	Supersedes date:	10/05/2012
Transportation version number:	2.00 (04/10/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M Scotchkote Urethane Elastomer 60EG 533 (Kit)

Product identification numbers

GR-2001-2066-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

28-4284-7, 29-1401-8, 28-5988-2

TRANSPORTATION INFORMATION

GR-2001-2066-9

Component 1

ADR/RID: UN1263, PAINT RELATED MATERIAL, LIMITED QUANTITY, 3., II , (E), ADR Classification Code: F1.

IMDG-CODE: UN1263, PAINT RELATED MATERIAL, 3, II , LIMITED QUANTITY, EMS: FE,SE.

ICAO/IATA: UN1263, PAINT RELATED MATERIAL, 3., II .

Component 2

3M Scotchkote Urethane Elastomer 60EG 533 (Kit)

ADR/RID: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. LIMITED QUANTITY, (DIETHYLMETHYLBENZENEDIAMINE), 9., III, (E), ADR Classification Code: M6.

IMDG-CODE: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIETHYLMETHYLBENZENEDIAMINE), 9., III, LIMITED QUANTITY, EMS: FA, SF.

ICAO/IATA: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIETHYLMETHYLBENZENEDIAMINE), 9., III, fish and tree marking may be required (> 5kg/l).

KIT LABEL

2.2. Label elements

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Highly
Flammable



Harmful



Dangerous
for the
environment

Contains:

Consult the component labels for disclosable ingredients.

Risk phrases

R11	Highly flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R42/43	May cause sensitisation by inhalation and skin contact.
R67	Vapours may cause drowsiness and dizziness.
R40	Limited evidence of a carcinogenic effect.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety phrases

S16	Keep away from sources of ignition - No Smoking.
S23A	Do not breathe vapour.
S36/37	Wear suitable protective clothing and gloves.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

Special provisions concerning the labelling of certain substances

Contains isocyanates. See information supplied by manufacturer.

Revision information:

Revision Changes:

Section 2: Risk phrase information information was modified.

Section 1: Product identification numbers information was modified.

Copyright information was modified.

Label: Graphic Text information was added.

Label: Graphic Text information was added.

Label: Graphic information was added.

Label: Graphic information was added.

Label: Graphic Text information was added.

3M Scotchkote Urethane Elastomer 60EG 533 (Kit)

Section 2: Symbol information was deleted.

Section 2: Symbols heading information was deleted.



Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-1401-8	Version number:	8.00
Revision date:	11/04/2014	Supersedes date:	24/02/2014
Transportation version number:	1.00 (16/02/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotchkote Urethane Elastomer Primer 075

Product Identification Numbers

GR-2001-0972-0 GR-2001-0973-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Carcinogenicity, Category 2 - Carc. 2; H351

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Highly flammable; F; R11
Carcinogenic; Carc. Cat. 3; R40
Irritant; Xi; R36/37/38
Sensitizing; R42/43
R67

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER!

Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms



Ingredient	CAS Nbr	% by Wt
Butanone	78-93-3	70 - 80
4,4'-methylenediphenyl diisocyanate	101-68-8	1 - 5
Diphenylmethane-2,4'-diisocyanate	5873-54-1	1 - 5

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

PRECAUTIONARY STATEMENTS

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P284A	In case of inadequate ventilation wear respiratory protection.
P280E	Wear protective gloves.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3M Scotchkote Urethane Elastomer Primer 075

P333 + P313
P370 + P378G

If skin irritation or rash occurs: Get medical advice/attention.
In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

25% of the mixture consists of components of unknown acute inhalation toxicity.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Highly
Flammable



Harmful

Contains:

Diphenylmethane-2,4'-diisocyanate; 4,4'-methylenediphenyl diisocyanate

Risk phrases

R11 Highly flammable.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitisation by inhalation and skin contact.
R67 Vapours may cause drowsiness and dizziness.
R40 Limited evidence of a carcinogenic effect.

Safety phrases

S16 Keep away from sources of ignition - No Smoking.
S23A Do not breathe vapour.
S36/37 Wear suitable protective clothing and gloves.
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Special provisions concerning the labelling of certain substances

Contains isocyanates. See information supplied by manufacturer.

2.3. Other hazards

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Butanone	78-93-3	EINECS 201-159-0	70 - 80	F:R11; Xi:R36; R66; R67 (EU) Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066 (CLP)
Non-hazardous ingredients	Mixture		15 - 30	
4,4'-methylenediphenyl diisocyanate	101-68-8	EINECS 202-966-0	1 - 5	Carc.Cat.3:R40; Xn:R20-48/20; Xi:R36-37-38; R42-43 - Nota 2,C (EU) Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;

3M Scotchkote Urethane Elastomer Primer 075

				Resp. Sens. 1, H334; Skin Sens. 1, H317; Carc. 2, H351; STOT SE 3, H335; STOT RE 2, H373 - Nota 2,C (CLP)
Diphenylmethane-2,4'-diisocyanate	5873-54-1	EINECS 227-534-9	1 - 5	Carc.Cat.3:R40; Xn:R20-48/20; Xi:R36-37-38; R42-43 - Nota 2,C (EU) Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Resp. Sens. 1, H334; Skin Sens. 1, H317; Carc. 2, H351; STOT SE 3, H335; STOT RE 2, H373 - Nota 2,C (CLP)

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Condition

During combustion.

3M Scotchkote Urethane Elastomer Primer 075

Carbon dioxide.
Hydrogen cyanide.
Oxides of nitrogen.

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	101-68-8	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
Free isocyanates	101-68-8	Health and Safety Comm. (UK)	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer
Free isocyanates	5873-54-1	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
Free isocyanates	5873-54-1	Health and Safety Comm. (UK)	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer
Butanone	78-93-3	Health and Safety Comm. (UK)	TWA: 600 mg/m ³ (200 ppm); STEL: 899 mg/m ³ (300 ppm)	Skin Notation

Health and Safety Comm. (UK) : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
Butanone	78-93-3	UK EH40 BMGVs	Butan-2-one	Urine	EOS	70 umol/L	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Polymer laminate

3M Scotchkote Urethane Elastomer Primer 075

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Appearance/Odour	Pungent Solvent odour; Clear Amber colour
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	>=80 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	-7 °C [<i>Test Method:Closed Cup</i>]
Autoignition temperature	515 °C
Flammable Limits(LEL)	1.8 % volume
Flammable Limits(UEL)	11.5 % volume
Vapour pressure	10,399.1 Pa [<i>@ 20 °C</i>]
Relative density	0.870 [<i>Ref Std:WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	2.7 [<i>Ref Std:BUOAC=1</i>]
Vapour density	2.5 [<i>Ref Std:AIR=1</i>]
Decomposition temperature	<i>No data available.</i>
Viscosity	< 0.001 Pa-s
Density	0.87 g/ml

9.2. Other information

Volatile organic compounds (VOC)	652.5 g/l
Percent volatile	75 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

Temperatures above the boiling point.

10.5 Incompatible materials

Alcohols.

Combustibles.

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause target organ effects after inhalation.

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

3M Scotchkote Urethane Elastomer Primer 075

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Butanone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Butanone	Ingestion	Rat	LD50 2,737 mg/kg
Diphenylmethane-2,4'-diisocyanate	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
4,4'-methylenediphenyl diisocyanate	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Diphenylmethane-2,4'-diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Diphenylmethane-2,4'-diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.369 mg/l
Diphenylmethane-2,4'-diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.369 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Butanone	Rabbit	Minimal irritation
Diphenylmethane-2,4'-diisocyanate	official classification	Irritant
4,4'-methylenediphenyl diisocyanate	official classification	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Butanone	Rabbit	Severe irritant
Diphenylmethane-2,4'-diisocyanate	official	Severe irritant

3M Scotchkote Urethane Elastomer Primer 075

	classification	
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant

Skin Sensitisation

Name	Species	Value
Diphenylmethane-2,4'-diisocyanate	official classification	Sensitising
4,4'-methylenediphenyl diisocyanate	official classification	Sensitising

Respiratory Sensitisation

Name	Species	Value
Diphenylmethane-2,4'-diisocyanate	Human	Sensitising
4,4'-methylenediphenyl diisocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Butanone	In Vitro	Not mutagenic
Diphenylmethane-2,4'-diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Butanone	Inhalation	Human	Not carcinogenic
Diphenylmethane-2,4'-diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Butanone	Inhalation	Not toxic to female reproduction	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Inhalation	Not toxic to male reproduction	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	LOAEL 8.8 mg/l	during gestation
Diphenylmethane-2,4'-diisocyanate	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-methylenediphenyl diisocyanate	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Butanone	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	

3M Scotchkote Urethane Elastomer Primer 075

			data are not sufficient for classification		available	
Butanone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable
Butanone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,080 mg/kg	not applicable
Diphenylmethane-2,4'-diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Butanone	Dermal	nervous system	All data are negative	Guinea pig	NOAEL Not available	31 weeks
Butanone	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Inhalation	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles	All data are negative	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	7 days
Butanone	Ingestion	nervous system	All data are negative	Rat	NOAEL 173 mg/kg/day	90 days
Diphenylmethane-2,4'-diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
Butanone	78-93-3	Green algae	Experimental	72 hours	NOEC	93 mg/l
Butanone	78-93-3	Ricefish	Experimental	96 hours	LC50	>100 mg/l

3M Scotchkote Urethane Elastomer Primer 075

4,4'-methylenediphenyl diisocyanate	101-68-8		Data not available or insufficient for classification			
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Water flea	Estimated	24 hours	EC50	>500 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Butanone	78-93-3	Experimental Biodegradation	20 days	BOD	89 % weight	Other methods
Butanone	78-93-3	Estimated Photolysis		Photolytic half-life (in air)	2.8 days (t 1/2)	Other methods
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Estimated Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Estimated Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.29	Other methods
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental BCF-Carp	28 days	Bioaccumulation factor	200	Other methods
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Estimated BCF-Carp	28 days	Bioaccumulation factor	200	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

080501* Waste isocyanates

SECTION 14: Transportation information

GR-2001-0972-0, GR-2001-0973-8

ADR/RID: UN1263, PAINT RELATED MATERIAL, LIMITED QUANTITY, 3., II, (E), ADR Classification Code: F1.

IMDG-CODE: UN1263, PAINT RELATED MATERIAL, 3, II, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FE,SE.

ICAO/IATA: UN1263, PAINT RELATED MATERIAL, 3., II.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
Diphenylmethane-2,4'-diisocyanate	5873-54-1	Carc.Cat.3	Regulation (EC) No. 1272/2008, Table 3.2
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc.Cat.3	Regulation (EC) No. 1272/2008, Table 3.2
4,4'-methylenediphenyl diisocyanate	101-68-8	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

List of relevant R-phrases

R11	Highly flammable.
R20	Harmful by inhalation.
R36	Irritating to eyes.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R42	May cause sensitisation by inhalation.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Revision information:

Revision Changes:

- Section 1: Product identification numbers heading information was modified.
- Section 3: Composition/ Information of ingredients table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12: Bioaccumulative potential information information was modified.
- CLP: Ingredient table information was modified.
- Section 11: Acute Toxicity table information was modified.
- Legend description information was added.
- BLV Reg Agency Desc information was added.
- Section 8: 8.1.1 Biological limit values table heading information was added.
- Section 8: BLV table information was added.
- Section 8: BLV table ingredient column heading information was added.
- Section 8: BLV table cas nbr column heading information was added.
- Section 8: BLV table agency column heading information was added.
- Section 8: BLV table cas nbr column heading information was added.
- Section 8: BLV table biological specimen Column heading information was added.
- Section 8: BLV table sampling time Column heading information was added.
- Section 8: BLV table value Column heading information was added.
- Section 8: BLV table additional comments Column heading information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4284-7	Version number:	5.00
Revision date:	14/08/2014	Supersedes date:	02/08/2013
Transportation version number:	1.00 (08/11/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

Product Identification Numbers

GR-2001-0956-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334
Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Harmful; Xn; R20
Sensitizing; R42/43

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER!

Symbols:

GHS08 (Health Hazard) |

Pictograms



Ingredient	CAS Nbr	% by Wt
Polypropylene Glycol-Isophorone Diisocyanate copolymer	39323-37-0	85 - 95
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	< 1.7

HAZARD STATEMENTS:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.
P284A In case of inadequate ventilation wear respiratory protection.
P280E Wear protective gloves.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains 91% of components with unknown hazards to the aquatic environment.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Harmful

Contains:

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Polypropylene Glycol-Isophorone Diisocyanate copolymer

Risk phrases

R20 Harmful by inhalation.
R42/43 May cause sensitisation by inhalation and skin contact.

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

Safety phrases

S23A	Do not breathe vapour.
S24	Avoid contact with skin.
S37	Wear suitable gloves.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Special provisions concerning the labelling of certain substances

Contains isocyanates. See information supplied by manufacturer.

2.3. Other hazards

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Polypropylene Glycol-Isophorone Diisocyanate copolymer	39323-37-0		85 - 95	R43 (Vendor) Skin Sens. 1, H317 (Vendor)
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	EINECS 223-861-6	< 1.7	T:R23; Xi:R36-37-38; N:R51/53; R42-43 - Nota 2 (EU) Acute Tox. 1, H330; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 2, H411 - Nota 2 (CLP)
Non-Hazardous Ingredients	Mixture		1 - 10	

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Clean up residue with detergent and water. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	4098-71-9	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
Free isocyanates	4098-71-9	Health and Safety Comm. (UK)	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer

Health and Safety Comm. (UK) : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve

Gloves made from the following material(s) are recommended: Nitrile rubber.

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Appearance/Odour	Musty odour; Opaque colour
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	≥ 100 °C
Melting point	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	≥ 100 °C [<i>Test Method: Closed Cup</i>]
Autoignition temperature	≥ 400 °C
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	2,266.5 Pa [<i>@ 25 °C</i>]
Relative density	1.08 [<i>Ref Std: WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.08 g/ml

9.2. Other information

Volatile organic compounds (VOC)	0 g/l [<i>Test Method: Estimated</i>] [<i>Details: EU Definition (Part A and B mix)</i>]
Percent volatile	0 % weight

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Accelerators

Alcohols.

Amines.

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Non-Hazardous Ingredients	Dermal	Rabbit	LD50 > 5,000 mg/kg
Non-Hazardous Ingredients	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Non-Hazardous Ingredients	Ingestion	Rat	LD50 > 5,110 mg/kg
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Dermal	Rat	LD50 > 7,000 mg/kg
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.03 mg/l
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Ingestion	Rat	LD50 4,815 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Non-Hazardous Ingredients	Rabbit	No significant irritation
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Non-Hazardous Ingredients	Rabbit	No significant irritation
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Non-Hazardous Ingredients	Human and animal	Not sensitizing
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Guinea pig	Sensitising

Respiratory Sensitisation

Name	Species	Value
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Non-Hazardous Ingredients	In Vitro	Not mutagenic
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	In vivo	Not mutagenic
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Non-Hazardous Ingredients	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Non-Hazardous Ingredients	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Non-Hazardous Ingredients	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Non-Hazardous Ingredients	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation	Not toxic to female reproduction	Rat	NOAEL 0.004 mg/l	during gestation
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation	Not toxic to male reproduction	Rat	NOAEL 0.004 mg/l	4 weeks
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.001 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Dermal	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 7,000 mg/kg	24 hours
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL 0.00025 mg/l	4 weeks
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL Not available	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Non-Hazardous Ingredients	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.00025 mg/l	4 weeks

Aspiration Hazard

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Non-Hazardous Ingredients	Mixture		Data not available or insufficient for classification			
Polypropylene Glycol-Isophorone Diisocyanate copolymer	39323-37-0		Data not available or insufficient for classification			

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Green algae	Experimental	72 hours	EC50	37 mg/l
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Water flea	Experimental	21 days	NOEC	3 mg/l
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Golden Orfe	Experimental	96 hours	LC50	110 mg/l
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Green algae	Experimental	72 hours	NOEC	1.5 mg/l
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Water flea	Experimental	48 hours	LC50	17.4 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polypropylene Glycol-Isophorone Diisocyanate copolymer	39323-37-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polypropylene Glycol-	39323-37-0	Data not available or	N/A	N/A	N/A	N/A

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

Isophorone Diisocyanate copolymer		insufficient for classification				
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3-Isocyanatomet hyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	Experimental BCF-Carp	42 days	Bioaccumulation factor	<3.4	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

080501* Waste isocyanates

SECTION 14: Transportation information

GR-2001-0956-3

Not hazardous for transportation

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

3M Scotchkote Urethane Elastomer 60EG 533 (Part A)

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

List of relevant R-phrases

R20	Harmful by inhalation.
R23	Toxic by inhalation.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R42	May cause sensitisation by inhalation.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Revision information:

Revision Changes:

Section 8: Skin protection - recommended gloves information information was modified.

Section 8: Personal Protection - Skin/body information information was modified.

Section 8: Skin protection - protective clothing information information was modified.

Section 1: Product identification numbers heading information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Copyright information was modified.

Section 8: Occupational exposure limit table information was modified.

Telephone header information was modified.

Company Telephone information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Respiratory Sensitization Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 6: Accidental release personal information information was modified.
Section 6: Accidental release clean-up information information was modified.
Section 7: Precautions safe handling information information was modified.
Section 7: Conditions safe storage information was modified.
Section 8: Personal Protection - Eye information information was modified.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 8: Personal Protection - Respiratory Information information was modified.
Section 13: 13.1. Waste disposal note information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.
Label: Signal Word - Header information was added.
Label: Signal Word information was added.
Label: CLP Classification - Header information was added.
Label: CLP Classification information was added.
Label: CLP Classification information was added.
Label: CLP Classification - Header information was added.
Label: CLP Percent Unknown information was added.
Label: Graphic information was added.
Label: Graphic information was added.
Label: Symbol information was added.
Label: Symbol information was added.
Label: CLP Precautionary - Prevention information was added.
Label: CLP Precautionary - Prevention - Header information was added.
Label: CLP Precautionary - Response information was added.
Label: CLP Precautionary - Response - Header information was added.
Label: Precautionary Statement - Header information was added.
CLP: Ingredient table information was added.
Section 2: 2.2 & 2.3. CLP REGULATION heading information was added.
Label: CLP Ingredients table Ingredient heading information was added.
Label: CLP Ingredients table CAS No heading information was added.
Label: CLP Ingredients table Percent by Wt heading information was added.
Section 2: H phrase reference information was added.
Section 10: Hazardous decomposition products during combustion text information was added.
Section 11: Disclosed components not in tables text information was added.
Section 12: Classification Warning information was added.
Section 11: Classification disclaimer information was added.
Section 8: 8.1.1 Biological limit values table heading information was added.
Section 8: BLV information was added.
Section 8: Eye/face protection text information was deleted.
Section 8: Respiratory protection - recommended respirators information was deleted.
Section 8: Skin protection - protective clothing text information was deleted.
Section 8: mg/m³ key information was deleted.
Section 8: ppm key information was deleted.
Section 11: Aspiration Hazard Table information was deleted.
Section 11: Classification disclaimer information was deleted.

Section 11: Target Organ Effects heading information was deleted.
Section 11: Health Effects - Other information information was deleted.
Section 12: Classification Warning information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-5988-2	Version number:	4.00
Revision date:	13/08/2014	Supersedes date:	17/09/2013
Transportation version number:	3.00 (09/12/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Product Identification Numbers

GR-2001-0955-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Dangerous for the environment; N; R51/53

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Symbols:

GHS09 (Environment) |

Pictograms



HAZARD STATEMENTS:

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

5% of the mixture consists of components of unknown acute oral toxicity.

5% of the mixture consists of components of unknown acute dermal toxicity.

Contains 7% of components with unknown hazards to the aquatic environment.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Dangerous
for the
environment

Contains:

No ingredients are assigned to the label.

Risk phrases

R51/53 Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety phrases

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Notes on labelling

.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)**2.3. Other hazards**

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Glycerol, propoxylated	25791-96-2	NLP 500-044-5	20 - 30	
Calcium Carbonate	471-34-1	EINECS 207-439-9	10 - 20	
Synthetic amorphous silica, fumed, crystalline free	112945-52-5		1 - 10	
Diethylmethylbenzenediamine	68479-98-1	EINECS 270-877-4	1 - 10	Xn:R21-22-48/22; Xi:R36; N:R50/53 - Nota C (EU) Acute Tox. 4, H312; Acute Tox. 4, H302; Eye Irrit. 2, H319; STOT RE 2, H373; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1 - Nota C (CLP)
Non-Hazardous Ingredients	Mixture		1 - 5	
proprietary zinc compounds	Trade Secret		1 - 5	
Bismuth(3+) neodecanoate	34364-26-6	EINECS 251-964-6	< 5	
Diisononyl Phthalate	28553-12-0	EINECS 249-079-5	1 - 5	
Propane-1,2-diol, propoxylated	25322-69-4	NLP 500-039-8	1 - 5	Xn:R22 (Self Classified) Acute Tox. 4, H302 (Self Classified)
Polyethylene Glycol	25322-68-3		1 - 5	
Carbon black	1333-86-4	EINECS 215-609-9	0.5 - 5	

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	112945-52-5	Health and Safety Comm. (UK)	TWA(as inhalable dust):6 mg/m ³ ;TWA(as respirable dust):2.4 mg/m ³	
Carbon black	1333-86-4	Health and Safety Comm. (UK)	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Diisononyl Phthalate	28553-12-0	Health and Safety Comm. (UK)	TWA:5 mg/m ³	
Limestone	471-34-1	Health and Safety Comm. (UK)	TWA(as inhalable dust):10 mg/m ³ ;TWA(as respirable dust):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	

Health and Safety Comm. (UK) : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Appearance/Odour	Slight odour; Black colour
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	≥ 100 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	100 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	≥ 400 °C
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	1.150 [<i>Test Method</i> :Estimated]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.15 g/ml

9.2. Other information

Volatile organic compounds (VOC)	0 g/l [<i>Test Method</i> :Estimated] [<i>Details</i> :EU Definition (Part A and B mix)]
Percent volatile	0 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Accelerators

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

May cause target organ effects after ingestion.

Target Organ Effects:

Prolonged or repeated exposure may cause:

Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Endocrine effects: Signs/symptoms may include disruption of gonadal, thyroid, adrenal, or pancreatic function, changes in hormone production, alterations in circulating hormone levels, and/or changes in tissue response to hormones.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Additional information:

Increased numbers of tumors in the liver, thyroid, and possibly the mammary glands were observed in rats given DETDA (CAS No. 68479-98-1) in their diet for two years.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Glycerol, propoxylated	Dermal	Rabbit	LD50 > 2,000 mg/kg
Glycerol, propoxylated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Glycerol, propoxylated	Ingestion	Rat	LD50 4,600 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.0 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Diethylmethylbenzenediamine	Dermal	Rat	LD50 > 2,000 mg/kg
Diethylmethylbenzenediamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.61 mg/l
Diethylmethylbenzenediamine	Ingestion	Rat	LD50 472 mg/kg
Propane-1,2-diol, propoxylated	Dermal	Rabbit	LD50 > 10,000 mg/kg
Propane-1,2-diol, propoxylated	Ingestion	Rat	LD50 1,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Rat	LD50 > 5,110 mg/kg
Diisononyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisononyl Phthalate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.7 mg/l
Diisononyl Phthalate	Ingestion	Rat	LD50 > 10,000 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diethylmethylbenzenediamine	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
Diisononyl Phthalate	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Minimal irritation
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product		Moderate irritant
Calcium Carbonate	Rabbit	No significant irritation
Diethylmethylbenzenediamine	Rabbit	Severe irritant
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Diisononyl Phthalate	Rabbit	Mild irritant
Polyethylene Glycol	Rabbit	Mild irritant
Carbon black	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Diethylmethylbenzenediamine	Human	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	Human and animal	Not sensitizing
Diisononyl Phthalate	Human and animal	Not sensitizing
Polyethylene Glycol	Guinea pig	Not sensitizing

Respiratory Sensitisation

Name	Species	Value
------	---------	-------

Germ Cell Mutagenicity

Name	Route	Value
Diethylmethylbenzenediamine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diethylmethylbenzenediamine	In vivo	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	In Vitro	Not mutagenic
Diisononyl Phthalate	In Vitro	Not mutagenic
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Diethylmethylbenzenediamine	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Diisononyl Phthalate	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Diethylmethylbenzenediamine	Ingestion	Not toxic to female reproduction	Rat	NOAEL 3.5 mg/kg/day	24 months
Diethylmethylbenzenediamine	Ingestion	Not toxic to male reproduction	Rat	NOAEL 2.8 mg/kg/day	24 months
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed,	Ingestion	Not toxic to development	Rat	NOAEL	during

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

crystalline free				1,350 mg/kg/day	organogenesis
Diisononyl Phthalate	Ingestion	Not toxic to female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Diisononyl Phthalate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Diisononyl Phthalate	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
Polyethylene Glycol	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not toxic to male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
Polyethylene Glycol	Not specified.	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		NOEL N/A	
Polyethylene Glycol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 562 mg/animal/day	during gestation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
Polyethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Diethylmethylbenzenedia mine	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/kg/day	24 months
Diethylmethylbenzenedia mine	Ingestion	endocrine system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 1.4 mg/kg/day	24 months
Diethylmethylbenzenedia mine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.8 mg/kg/day	24 months
Diethylmethylbenzenedia mine	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.4 mg/kg/day	24 months
Diethylmethylbenzenedia mine	Ingestion	heart skin bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system respiratory system	All data are negative	Rat	NOAEL 3.5 mg/kg/day	24 months
Synthetic amorphous silica, fumed, crystalline free	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
Diisononyl Phthalate	Dermal	blood liver kidney and/or bladder	All data are negative	Rabbit	NOAEL 2,425 mg/kg/day	6 weeks
Diisononyl Phthalate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	13 weeks

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Polyethylene Glycol	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Polyethylene Glycol	Ingestion	heart endocrine system hematopoietic system liver nervous system	All data are negative	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Carbon black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
------	-------

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Bismuth(3+) neodecanoate	34364-26-6		Data not available or insufficient for classification			
Glycerol, propoxylated	25791-96-2	Ricefish	Experimental	48 hours	LC50	630 mg/l
Diisononyl Phthalate	28553-12-0		Data not available or insufficient for classification			
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Water flea	Analogous Compound	48 hours	EC50	7,600 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Zebra Fish	Analogous Compound	96 hours	LC50	5,000 mg/l
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Green algae	Analogous Compound	72 hours	EC50	440 mg/l
Diethylmethyl benzenediamine	68479-98-1	Golden Orfe	Experimental	48 hours	LC50	194 mg/l

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Diethylmethyl benzenediamine	68479-98-1	Water flea	Experimental	48 hours	EC50	0.5 mg/l
Propane-1,2-diol, propoxylated	25322-69-4	Inland Silverside	Laboratory	96 hours	LC50	650 mg/l
Polyethylene Glycol	25322-68-3	Atlantic Salmon	Experimental	96 hours	LC50	>1,000 mg/l
Calcium Carbonate	471-34-1	Western Mosquitofish	Experimental	96 hours	LC50	>100 mg/l
Calcium Carbonate	471-34-1	Rainbow trout	Experimental	21 days	NOEC	>100 mg/l
Carbon black	1333-86-4		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Bismuth(3+) neodecanoate	34364-26-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol, propoxylated	25791-96-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisononyl Phthalate	28553-12-0	Experimental Biodegradation	28 days	BOD	74 % weight	OECD 301C - MITI test (I)
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diethylmethyl benzenediamine	68479-98-1	Experimental Biodegradation	28 days	BOD	<1 % weight	OECD 301D - Closed bottle test
Propane-1,2-diol, propoxylated	25322-69-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethylene Glycol	25322-68-3	Experimental Biodegradation	28 days	BOD	56.2 % weight	OECD 301C - MITI test (I)
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Bismuth(3+) neodecanoate	34364-26-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol, propoxylated	25791-96-2	Experimental BCF-Carp	42 days	Bioaccumulation factor	<7	Other methods
Diisononyl Phthalate	28553-12-0	Analogous Compound BCF - Other	56 days	Bioaccumulation factor	<14.4	Other methods
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diethylmethyl benzenediamine	68479-98-1	Estimated Bioconcentration		Bioaccumulation factor	9.0	Estimated: Bioconcentration factor
Propane-1,2-diol, propoxylated	25322-69-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethylene Glycol	25322-68-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

GR-2001-0955-5

ADR/RID: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. LIMITED QUANTITY, (DIETHYLMETHYLBENZENEDIAMINE), 9., III, (E), ADR Classification Code: M6.

IMDG-CODE: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIETHYLMETHYLBENZENEDIAMINE), 9., III, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FA, SF.

ICAO/IATA: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIETHYLMETHYLBENZENEDIAMINE), 9., III, fish and tree marking may be required (> 5kg/l).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

List of relevant R-phrases

R21 Harmful in contact with skin.
R22 Harmful if swallowed.
R36 Irritating to eyes.
R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R50/53 Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R51/53 Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Revision information:

Revision Changes:

Section 8: Skin protection - recommended gloves information information was modified.
Section 8: Respiratory protection - recommended respirators information information was modified.
Section 1: Product identification numbers heading information was modified.
Section 3: Composition/ Information of ingredients table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Copyright information was modified.
Section 8: Occupational exposure limit table information was modified.
Telephone header information was modified.
Company Telephone information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 8: Personal Protection - Eye information information was modified.
Section 13: 13.1. Waste disposal note information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.
Label: CLP Classification - Header information was added.
Label: CLP Classification information was added.
Label: CLP Classification - Header information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Environmental Hazard Statements information was added.
Label: Graphic information was added.
Label: Graphic information was added.
Label: Symbol information was added.
Label: Symbol information was added.
Label: CLP Precautionary - Disposal information was added.
Label: CLP Precautionary - Disposal - Header information was added.
Label: CLP Precautionary - Prevention information was added.
Label: CLP Precautionary - Prevention - Header information was added.
Label: Precautionary Statement - Header information was added.

3M Scotchkote Urethane Elastomer 60EG 533 (Part B)

Section 11: Additional information heading information was added.
Section 11: Health Effects - Additional Information information was added.
Section 2: 2.2 & 2.3. CLP REGULATION heading information was added.
Section 8: Personal Protection - Skin/hand information information was added.
Section 8: Personal Protection - Respiratory Information information was added.
Section 2: H phrase reference information was added.
Section 11: Disclosed components not in tables text information was added.
Section 12: Classification Warning information was added.
Section 11: Classification disclaimer information was added.
Section 8: 8.1.1 Biological limit values table heading information was added.
Section 8: BLV information was added.
Section 8: Eye/face protection text information was deleted.
Section 8: Personal Protection - Skin/body information information was deleted.
Section 8: Respiratory protection - recommended respirators information was deleted.
Section 8: Skin protection - protective clothing information information was deleted.
Section 8: Skin protection - protective clothing text information was deleted.
Section 11: Aspiration Hazard Table information was deleted.
Section 11: Classification disclaimer information was deleted.
Section 11: Respiratory Sensitization Table information was deleted.
Section 12: Classification Warning information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk