

ISO-9001 Registered Quality System.

#### Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

## **PRODUCT DATA**

# **LUBRIPLATE "630" SERIES**

#### DESCRIPTION

A series of Lithium-based greases for general purpose lubricants for food processing equipment, as well as industrial applications. With one series of products, inventory and purchasing can be consolidated with LUBRIPLATE "630" greases.

#### **ADVANTAGES**

- ⇒ Excellent grease mobility in constant service applications
- ⇒ High anti-wear for extra lubricity
- ⇒ Oxidation inhibited
- ⇒ Wide operating temperature range

### **APPLICATIONS**

**LUBRIPLATE No 630-AAA**: as an NLGI No. 0 lubricant, is ideal for centralized lubricating systems. Also excellent for certain types of enclosed gear cases (medium speed – no seals) as the lubricant will re-feed itself into the gear train.

**LUBRIPLATE No. 630-AA**: is an NLGI No. 1 lubricant and the most popular multipurpose general grease. Ideal for automatic dispensing systems, and centralized systems with large lines.

**LUBRIPLATE No. 630-A**: is a heavy type NLGI No. 2.5 lubricant for applications requiring a cup type lubricant. Excellent for water pumps.

**LUBRIPLATE No. 630-2**: is an NLGI No. 2 lubricant and the ideal grease gun lubricant for general greasing. LUBRIPLATE No. 630-2 is available in the convenient 14 1/2 oz. grease gun cartridge.



# **Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*			
		630- AAA	630- AA	630-A	630-2
Type of Soap		Lithium	Lithium	Lithium	Lithium
NLGI No.		0	1	2.5	2
Worked Penetration Range	ASTM D-217	355/385	310/340	235/260	265/295
Dropping Point	ASTM D-566	360°F 182°C	380°F 193°C	390°F 199°C	380°F 193°C
Viscosity SUS @ 100°F	ASTM D-2161	800	750	750	750
cSt @ 40°C	ASTM D-445	151	135	135	135
Color	Visual	Off- White	Off- White	Off- White	Off- White

Packaging Available	630-AAA	630-AA
Carton, 12/16 oz. Plastic Tubs	L0068-004	L0067-004
Carton, 6/6 lb. Cans	L0068-006	L0067-006
35 lb. Pail	L0068-035	L0067-035
115 lb. Quarter Size Drum	L0068-039	***
120 lb. Quarter Size Drum	***	L0067-039
Full Size Drum	L0068-040	L0067-040
Carton, 288 - 3/8 oz Tubes	***	L0067-076
Carton, 144/1¾ oz. Tubes (1x6)	***	L0067-086
Carton, 36/10 oz. Plastic Tubes	***	L0067-092
Carton, 40/141/2 oz. Cartridges	***	***
Oarton, 40/14/2 02. Cartiluges		
Packaging Available	630-A	630-2
_	<b>630-A</b> L0066-004	<b>630-2</b> L0072-004
Packaging Available		
Packaging Available Carton, 12/16 oz. Plastic Tubs	L0066-004	L0072-004
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans	L0066-004 L0066-006	L0072-004 L0072-006
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans 35 lb. Pail	L0066-004 L0066-006 L0066-035	L0072-004 L0072-006 L0072-035
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans 35 lb. Pail 115 lb. Quarter Size Drum	L0066-004 L0066-006 L0066-035	L0072-004 L0072-006 L0072-035
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans 35 lb. Pail 115 lb. Quarter Size Drum 120 lb. Quarter Size Drum	L0066-004 L0066-006 L0066-035 ***	L0072-004 L0072-006 L0072-035 *** L0072-039
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans 35 lb. Pail 115 lb. Quarter Size Drum 120 lb. Quarter Size Drum Full Size Drum	L0066-004 L0066-035 *** L0066-039 L0066-040	L0072-004 L0072-035 *** L0072-039 L0072-040
Packaging Available Carton, 12/16 oz. Plastic Tubs Carton, 6/6 lb. Cans 35 lb. Pail 115 lb. Quarter Size Drum 120 lb. Quarter Size Drum Full Size Drum Carton, 288 - 3/8 oz Tubes	L0066-004 L0066-035 *** L0066-039 L0066-040	L0072-004 L0072-035 *** L0072-039 L0072-040 ***