

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOLYKOTE(R) MKL-N GREASE  
Product code : 000000000001206524, 000000000001206524

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricants and lubricant additives

#### 1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.  
rue Jules Bordet - Parc Industriel - Zone C  
B-7180 Seneffe

Telephone : English Tel: +49 611237507  
Deutsch Tel: +49 611237500  
Français Tel: +32 64511149  
Italiano Tel: +32 64511170  
Español Tel: +32 64511163

E-mail address of person responsible for the SDS : sdseu@dowcorning.com

#### 1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350  
Dow Corning (Wiesbaden 24h) Tél: +49 61122158  
Dow Corning (Seneffe 24h) Tel: +32 64 888240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2      H225: Highly flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3      H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

**MOLYKOTE(R) MKL-N GREASE**

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

Hazard statements : H225 Highly flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

Hazardous components which must be listed on the label:  
n-Butyl acetate

**2.3 Other hazards**

Static-accumulating flammable liquid.  
Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

Chemical nature : Inorganic and organic compounds  
Mixture

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7	Asp. Tox. 1; H304	>= 10 - < 20
Diphenyl- (2-ethylhexyl) - phosphate	1241-94-7 214-987-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0.25 - < 1



## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

Substances with a workplace exposure limit :			
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9	Flam. Liq. 3; H226	>= 10 - < 20

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items



## MOLYKOTE(R) MKL-N GREASE

---

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Technical measures : Ensure all equipment is electrically grounded before beginning transfer operations.  
This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations.  
Restrict flow velocity in order to reduce the accumulation of static electricity.
- Local/Total ventilation : Use with local exhaust ventilation.  
Use only in an area equipped with explosion proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapours or spray mist.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents  
Organic peroxides  
Flammable solids

**MOLYKOTE(R) MKL-N GREASE**

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

**7.3 Specific end use(s)**

Specific use(s)

: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	960 mg/m3

**MOLYKOTE(R) MKL-N GREASE**

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

	Workers	Inhalation	Acute local effects	960 mg/m3
	Workers	Inhalation	Long-term systemic effects	480 mg/m3
	Workers	Inhalation	Long-term local effects	480 mg/m3
	Consumers	Inhalation	Acute systemic effects	859.7 mg/m3
	Consumers	Inhalation	Acute local effects	859.7 mg/m3
	Consumers	Inhalation	Long-term systemic effects	102.34 mg/m3
	Consumers	Inhalation	Long-term local effects	102.34 mg/m3
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Skin contact	Long-term systemic effects	153.5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Skin contact	Long-term systemic effects	54.8 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1.67 mg/kg bw/day
Diphenyl- (2-ethylhexyl) -phosphate	Workers	Inhalation	Long-term systemic effects	5.11 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.73 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.54 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0.44 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.44 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	40.88 mg/m3
	Workers	Skin contact	Acute systemic effects	5.84 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	58.45 mg/m3
	Consumers	Skin contact	Acute systemic effects	52.67 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	16.7 mg/kg bw/day

**MOLYKOTE(R) MKL-N GREASE**

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Intermittent use/release	0.36 mg/l
	Sewage treatment plant	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.0981 mg/kg
	Soil	0.0903 mg/kg
2-Methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l
	Marine water	0.0635 mg/l
	Intermittent use/release	6.35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3.29 mg/kg
	Marine sediment	0.329 mg/kg
	Soil	0.29 mg/kg
Residual oils (petroleum), solvent-dewaxed	Oral	9.33 mg/kg
Diphenyl- (2-ethylhexyl) - phosphate	Fresh water	1.8 µg/l
	Marine water	0.18 µg/l
	Intermittent use/release	1.5 µg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	5.8 mg/kg
	Marine sediment	0.58 mg/kg
	Soil	1.16 mg/kg
	Oral	3.86 mg/kg

**8.2 Exposure controls**

**Engineering measures**

Minimize workplace exposure concentrations.  
Use only in an area equipped with explosion proof exhaust ventilation.  
Use with local exhaust ventilation.

**Personal protective equipment**

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Hand protection  
Material : Antistatic gloves



## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

	Impervious gloves Flame retardant gloves
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	: Combined particulates and organic vapour type (A-P)

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: black
Odour	: ester-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Flash point	: 22.5 °C Method: Tag closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available

## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.87

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-  
octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : 4000 mm<sup>2</sup>/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Molecular weight : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Highly flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.  
When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours.  
Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde.

### 10.4 Conditions to avoid

Conditions to avoid : Handling operations that can promote accumulation of static charges.  
Heat, flames and sparks.

## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

##### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

**Diphenyl- (2-ethylhexyl) -phosphate:**

Acute oral toxicity : LD50 (Rat): > 15,800 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 4.8 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

**2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

Species: Rabbit  
Result: Mild skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Diphenyl- (2-ethylhexyl) -phosphate:**

Species: Rabbit  
Result: No skin irritation

**2-Methoxy-1-methylethyl acetate:**

Species: Rabbit  
Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: No eye irritation  
Remarks: Based on data from similar materials

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: No eye irritation

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

---

Remarks: Based on data from similar materials

**Diphenyl- (2-ethylhexyl) -phosphate:**

Species: Rabbit  
Result: No eye irritation

**2-Methoxy-1-methylethyl acetate:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Result: negative  
Remarks: Based on data from similar materials

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative  
Remarks: Based on data from similar materials

**2-Methoxy-1-methylethyl acetate:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

Germ cell mutagenicity- As- : Classified based on benzene content < 0.1% (Regulation (EC))

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

assessment      1272/2008, Annex VI, Part 3, Note P)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Genotoxicity in vitro      : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo      : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Diphenyl- (2-ethylhexyl) -phosphate:**

Genotoxicity in vitro      : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo      : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Ingestion  
Result: negative

**2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro      : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 105 weeks  
Result: negative  
Remarks: Based on data from similar materials

Carcinogenicity - Assessment      : Classified based on benzene content < 0.1% (Regulation (EC)  
1272/2008, Annex VI, Part 3, Note P)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species: Mouse  
Application Route: Skin contact  
Exposure time: 78 weeks  
Method: OECD Test Guideline 451  
Result: negative

Carcinogenicity - Assessment      : Classified based on DMSO extract content < 3% (Regulation  
(EC) 1272/2008, Annex VI, Part 3, Note L)

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

---

### **2-Methoxy-1-methylethyl acetate:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 2 Years  
Result: negative  
Remarks: Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Naphtha (petroleum), hydrotreated heavy:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Skin contact  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

#### **Diphenyl- (2-ethylhexyl) -phosphate:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

---

Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **Components:**

##### **Naphtha (petroleum), hydrotreated heavy:**

Assessment: May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

#### **Components:**

##### **Naphtha (petroleum), hydrotreated heavy:**

Species: Rat  
NOAEL: 10,186 mg/m<sup>3</sup>  
Application Route: inhalation (vapour)  
Exposure time: 13 Weeks

##### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species: Rabbit  
NOAEL: 1,000 mg/kg  
Application Route: Skin contact  
Exposure time: 4 Weeks  
Method: OECD Test Guideline 410  
Remarks: Based on data from similar materials

Species: Rat  
NOAEL: > 980 mg/m<sup>3</sup>  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 4 Weeks  
Remarks: Based on data from similar materials

##### **Diphenyl- (2-ethylhexyl) -phosphate:**

Species: Rat  
LOAEL: 174 mg/kg  
Application Route: Ingestion  
Exposure time: 90 Days

##### **2-Methoxy-1-methylethyl acetate:**

Species: Rat  
NOAEL: > 1,000 mg/kg  
Application Route: Ingestion  
Exposure time: 41 - 45 Days



## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

---

Method: OECD Test Guideline 422

Species: Mouse  
NOAEL: 1.62 mg/l  
Application Route: inhalation (vapour)  
Exposure time: 2 yr  
Remarks: Based on data from similar materials

Species: Rabbit  
NOAEL: > 1,000 mg/kg  
Application Route: Skin contact  
Exposure time: 21 Days  
Remarks: Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
-

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to bacteria : NOEC : > 1.93 mg/l  
Exposure time: 10 min  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Diphenyl- (2-ethylhexyl) -phosphate:**

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Chironomus sp. (midge)): 0.67 mg/l  
Exposure time: 48 h
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 0.12 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOEC (Desmodesmus subspicatus (green algae)): 0.072 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to fish (Chronic toxicity) : NOEC: 0.021 mg/l  
Exposure time: 71 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.018 mg/l  
Exposure time: 21 d

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

ic toxicity)      Species: Daphnia magna (Water flea)

### **2-Methoxy-1-methylethyl acetate:**

Toxicity to fish      : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates      : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h

Toxicity to algae      : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to bacteria      : EC10 : > 1,000 mg/l  
Exposure time: 0.5 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      : NOEC: > 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

## 12.2 Persistence and degradability

### **Components:**

#### **Naphtha (petroleum), hydrotreated heavy:**

Biodegradability      : Result: Readily biodegradable  
Biodegradation: 89 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Biodegradability      : Result: Not readily biodegradable.  
Biodegradation: 2 - 8 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### **Diphenyl- (2-ethylhexyl) -phosphate:**

Biodegradability      : Result: Readily biodegradable  
Biodegradation: 70.8 %  
Exposure time: 15 d  
Method: OECD Test Guideline 301B

### **2-Methoxy-1-methylethyl acetate:**

Biodegradability      : Result: Readily biodegradable  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

---

### 12.3 Bioaccumulative potential

**Components:**

**Diphenyl- (2-ethylhexyl) -phosphate:**

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)  
Bioconcentration factor (BCF): 934

Partition coefficient: n-octanol/water : log Pow: 5.87

**2-Methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not burn, or use a cutting torch on, the empty drum.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1993

ADR : UN 1993

RID : UN 1993

IMDG : UN 1993

IATA : UN 1993

### 14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.  
(n-Butyl acetate, Naphtha (petroleum), hydrotreated heavy)

ADR : FLAMMABLE LIQUID, N.O.S.

---



## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

**RID** : (n-Butyl acetate, Naphtha (petroleum), hydrotreated heavy)  
: FLAMMABLE LIQUID, N.O.S.  
(n-Butyl acetate, Naphtha (petroleum), hydrotreated heavy)

**IMDG** : FLAMMABLE LIQUID, N.O.S.  
(n-Butyl acetate, Naphtha (petroleum), hydrotreated heavy)

**IATA** : Flammable liquid, n.o.s.  
(n-Butyl acetate, Naphtha (petroleum), hydrotreated heavy)

### 14.3 Transport hazard class(es)

**ADN** : 3

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341



## MOLYKOTE(R) MKL-N GREASE

Version 1.1      Revision Date: 01.10.2015      SDS Number: 1204637-00002      Date of last issue: 28.01.2015  
Date of first issue: 28.01.2015

Packing group : II  
Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : no

**ADR**  
Environmentally hazardous : no

**RID**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar	2,500 t	25,000 t

## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

properties as regards  
flammability and environ-  
mental hazards as the  
products referred to in  
points (a) to (d)

Other regulations : Take note of Dir 94/33/EC on the protection of young people at work.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

**The components of this product are reported in the following inventories:**

NZIoC : All ingredients listed or exempt.

REACH : All ingredients (pre-)registered or exempt.

IECSC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

PICCS : Consult your local Dow Corning office.

KECI : One or more ingredients are not listed or exempt.

ENCS/ISHL : Some components are not listed or not identified on ENCS/ISHL.

TCSI : All ingredients listed or exempt.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

#### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity

## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.



## MOLYKOTE(R) MKL-N GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2015
1.1	01.10.2015	1204637-00002	Date of first issue: 28.01.2015

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN