Regulation EC No 1907/2006 Art.31

Rust Flash Productname:

Ref.Nr.: BDS000204 3 20140915 (EN)

Creationdate: Replaces:

15.09.14 Version: 1.0 BDS000204 20110606

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rust Flash

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Health: Skin irritation, category 2

Causes skin irritation.

Environment: Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

Other hazards: None

Classification according to 67/548/EEC or 1999/45/EC:

EXTREMELY FLAMMABLE

Health: R67: Vapours may cause drowsiness and dizziness.



1/10

CRC Industries UK Limited

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Creationdate: 15.09.14 Version: 1.0 Ref.Nr.: BDS000204 3 20140915 (EN) BDS000204 20110606 Replaces:

EXTREMELY FLAMMABLE Physical:

Environment: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):





Signal word: Danger

Hazard statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

P102: Keep out of reach of children. Precautionary statement(s):

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 : Use only outdoors or in a well-ventilated area.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

information:

None

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.		70	-	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990- 9	50-70	F+	12	K,G
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	921-024- 6	10-20	F,Xn,N	11-38-51/53-65- 67	В
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47- 8	920-107- 4	5-10	Xn	65-66	В
mineral oil (IP 346 DMSO extract < 3%)	-	-	1-5	-	-	В



Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Creationdate: 15.09.14 Version: 1.0 BDS000204 3 20140915 (EN) BDS000204 20110606 Ref.Nr.: Replaces:

34590-94- 252-104-(2-methoxymethylethoxy)propanol 1-2.5

Explanation notes

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Hazardous ingredient	Registration number	CAS- nr.	EC- nr		Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	-	68512- 91-4	270- 990- 9	50- 70	Press. Gas, Flam. Gas 1	H280,H220	K,G
Hydrocarbons, C6-C7, n- alkanes,isoalkanes,cyclics,< 5% n- hexane	01- 2119475514- 35	-	921- 024- 6	10- 20	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	В
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	01- 2119453414- 43	64742- 47-8	920- 107- 4	5-10	Asp. Tox. 1	H304	В
mineral oil (IP 346 DMSO extract < 3%)		-	-	1-5	-	-	В
(2-methoxymethylethoxy)propanol	01- 2119450011- 60	34590- 94-8	252- 104- 2	1- 2.5	-	-	А

Explanation notes

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water

If eye irritation persists: Get medical advice/attention.

Contact with skin: Take off contaminated clothing and wash before reuse.

> IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

If swallowed do not induce vomiting because of risk of aspiration into the Ingestion:

lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.



Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Ref.Nr.: BDS000204_3_20140915 (EN)

Creationdate : Replaces:

15.09.14 Version : 1.0 BDS000204_20110606

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact : Irritating to skin

Symptoms: redness and pain

Eye contact : May cause irritation.

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Creationdate: 15.09.14 Version: 1.0 Ref.Nr.: BDS000204 3 20140915 (EN) Replaces: BDS000204 20110606

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm
National established exposure limits, United Kingdom			
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm

8.2. Exposure controls

Control	procedures:	Ensure	adequate	eventilation
---------	-------------	--------	----------	--------------

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equiped with organic gas/vapor cartridge (type A)

hands and skin: Wear suitable protective gloves against chemicals

Nitrile



Regulation EC No 1907/2006 Art.31

15.09.14 Version: 1.0

Creationdate:

Productname: Rust Flash

Ref.Nr.: BDS000204 3 20140915 (EN) BDS000204 20110606 Replaces:

eyes: Wear safety goggles.

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Propane/butane propelled liquid. Apperance : physical state :

colour: Amber.

odour: Characteristic odor. pH: Not applicable. Boiling point/range: 65-270 °C Flash point: < 0 °C Evaporation rate: Not available. Explosion limits: upper limit: Not available. Not available. lower limit: Vapour pressure : Not available. Relative density: 0.75 g/cm3 (@ 20°C).

Solubility in water : Insoluble in water Auto-ignition: Not available. Viscosity: Not available.

9.2. Other information

VOC: 94 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent



6/10

CRC Industries UK Limited

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Creationdate: 15.09.14 Version: 1.0 Ref.Nr.: BDS000204 3 20140915 (EN) Replaces: BDS000204 20110606

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Skin contact: Irritating to skin Eye contact: May cause irritation.

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
(2-methoxymethylethoxy)propanol	34590-94-8	LD50 oral rat	> 4000 mg/kg
		LD50 derm.rabit	9510 mg/kg
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 4951 mg/l
		LD50 derm.rabit	> 5000 mg/kg
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
(2-methoxymethylethoxy)propanol	34590-94-8	EC50 daphnia	1919 mg/l
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l

12.2. Persistence and degradability



Regulation EC No 1907/2006 Art.31

Productname: Rust Flash

Creationdate: 15.09.14 Version: 1.0 Ref.Nr.: BDS000204 3 20140915 (EN) Replaces: BDS000204 20110606

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

Contaminated packaging : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: **AEROSOLS**

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards



8 / 10

CRC Industries UK Limited

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

 Productname :
 Rust Flash
 Creationdate :
 15.09.14 Version : 1.0

 Ref.Nr.:
 BDS000204 3 20140915 (EN)
 Replaces:
 BDS000204 20110606

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant: No IATA/ICAO - Environmentally hazardous:

14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

Regulation (EC) No 1907/2006 (REACH)

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases: R11: Highly flammable.

R12: Extremely flammable.

R38: Irritating to skin.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

*Explanation hazard statements: -:-

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

Productname: Rust Flash Creationdate: 15.09.14 Version: 1.0 Ref.Nr.: BDS000204 3 20140915 (EN) Replaces: BDS000204 20110606

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

