

SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label Product identifier 33

Details of the supplier of the safety data sheet

3009 TECTYL® 506 Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638 708-496-7350 Chemtrec: (800) 424-9300 Corrosion Preventive Compound

Emergency telephone number Relevant identified uses of the substance or mixture and uses advised against

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification	Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2B Flammable Liquid Category 3 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Signal Word	Warning
Hazard Statements	Flammable liquid and vapour.
	Causes skin and eye irritation
	May cause respiratory irritation.
	May cause drowsiness or dizziness.
Precautionary Statements	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.
	D 1 67

Response	Revision Date 01-20-2016 Revision Number 11 Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell.
	Specific treatment: None known If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before
	reuse. Use dry chemical, water fog, CO2, foam or sand/earth for extinction.
Storage	Store in a well-ventilated place. Keep container tightly closed.
Disposal	Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients		
Chemical Name	CAS #	%
Hydrotreated light distillate (Petroleum)	64742-47-8	40 - 60

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures		
Inhalation	If symptoms are experienced rem	
	obtain medical advice.	

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and
	obtain medical advice.
Eyes	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to
	prevent chemical from transferring to the uncontaminated eye. Get immediate medical
	attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion	Do not induce vomiting and seek medical attention immediately. Provide medical care
-	provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration
	into lungs.
Note to Doctor	Treat symptomatically.

SECTION 5 Firefighting measures	
Extinguishing media Fire and/or Explosion Hazards	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder,
Fire Fighting Methods and Protection	drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.
Hazardous Combustion Products	Carbon dioxide, Carbon monoxide, Sulfur compounds, Hydrocarbons
SECTION 6 Accidental release measures	
Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleaning up	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.
SECTION 7 Handling and storage	
Precautions for safe handling Conditions for safe storage, including an incompatibilities Incompatible materials	 Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. y Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away from heat, sparks, and flame. Strong oxidizing agents, Strong acids

Revision Date 01-20-2016 Revision Number 11

SECTION 8 Exposure controls/personal protection

<u>Control parameters</u> <u>Chemical Name</u>		ACGIH TLV	ACGIH STEL	OSHA PEL
Hydrotreated light distillate	e (Petroleum)	179 ppm		500 ppm
Engineering Measures	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits			
Respiratory Protection	Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.			
Eye Protection	1	stant safety glasses with s		dling this product.
Skin Protection	practice good persona	ered a skin hazard. Where al hygiene and wear a bar ands and other exposed ar when leaving work.	rier cream and/or imp	ervious surgical
Gloves	Chemically resistant	gloves		

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Color Odor Odor Threshold pH Melting Point, °C Boiling Point, °C	Liquid Amber Slight Solvent Odor No data available No data available No data available No data available
Flash Point Evaporation Rate Flammability (Solid, Gas) Lower Flammable/Explosive Limit, % in air Upper Flammable/Explosive Limit,	>= 100 °F(38 °C) No data available No data available No data available
% in air Vapor Pressure Vapor Density Specific Gravity @ 25°C Solubility in Water Octanol/Water Partition Coefficient Autoignition Temperature	2 mmHg >1 (Air=1) 0.86 Negligible; 0-1% No data available No data available

TECTYL® 506

Revision Date 01-20-2016 Revision Number 11

Decomposition TemperatureNo daViscosity80 cSVolatiles, % by weight44VOC, lb/gal3.21VOC, grams/liter385.0VOC minus exempt solvents & water,
lb/gal3.21

No data available 80 cSt @ 40°C 44 3.21 285 0

SECTION 10 Stability and reactivity

Chemical stability	Stable under normal conditions. Hazardous polymerization will not occur.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contamination. Elevated temperatures.
Incompatible materials	Strong oxidizing agents, Strong acids
Hazardous decomposition products	Under normal conditions of use & storage, decomposition and
	hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry	Inhalation, Skin contact, Eye contact
Target Organs Potentially Affected by Exposure	Central Nervous System, Respiratory Tract, Skin, Eyes,
	Kidneys, Liver, Nervous System
Chemical Interactions That Change Toxicity	No chemical interaction known to affect toxicity.
Medical Conditions Aggravated	Skin contact may aggravate existing skin disease, Respiratory
	disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and
	headache. Other possible symptoms include; wheezing and coughing due to pulmonary
	edema (fluid build-up in lungs).
Skin Contact	Can cause minor skin irritation, defatting, and dermatitis.
Eye Contact	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity	Harmful if swallowed.
Long-Term (Chronic)	Health Effects

Carcinogenicity	Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.
Inhalation	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,
	dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and
	dermatitis.
Ingestion	Under normal industrial usage conditions, ingestion is highly unlikely.

Revision Date 01-20-2016 Revision Number 11

Component Toxicology Dat Chemical Name Hydrotreated light distillate (Petroleum)	a CAS Number 64742-47-8	LD50/LC50 Dermal LD50 Rabbit Inhalation LC50 (4h)	> 2000 mg/kg Oral LD50 F Rat > 20 mg/L	Rat > 5000 mg/kg		
SECTION 12 Ecological inform	nation					
Overview	No ecological information available					
Mobility	No data					
Persistence	No data					
Bioaccumulation	No data					
Degradability	No data					
Ecotoxicity Data						
Chemical Name	CAS Number	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish		
No data available						
SECTION 13 Disposal conside	rations					
Waste Description for Spent Product Disposal MethodsSpent or discarded material may be a hazardous waste. Dispose of by incineration following Federal, State, Local, or Provincial regulations.						
Waste Disposal Code(s)	D001					
SECTION 14 Transport inform	nation					
Full shipping name for Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more	UN1268, PETROL	EUM DISTILLATES	, N.O.S., (Naphtha Sol	vent), 3, PG III,		
Domestic Ground in vessels < 119 gal.	s < Not Regulated					
SECTION 15 Regulatory information						
Status of formula components on selected national regulatory inventories:						
LIST STATU	JS					

L151	SIAIUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	All chemical substances in this material are included on or exempted from listing on the
	Canadian DSL.

				Revision Date 01-20-2016 Revision Number 11			
Chemical Nar No CERCLA product.	ne -listed chemicals in this	CAS #	Regulation CERCLA	Percent			
No 313-listed chemicals in this			SARA 313				
product. No SARA 302 EHS-listed chemicals in this product.			SARA EHS				
SECTION 16 Other information							
Revision Date	01-20-2016						
Disclaimer	Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.						
Version Comments	Reviewed Approved: J. Kump						