

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Zinc Primer
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom
Tel.: +44 1278 727200
Fax.: +44 1278 425644
E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:	Aerosols, category 1 Extremely flammable aerosol. Pressurised container: May burst if heated.
Health:	Skin irritation, category 2 Causes skin irritation. Eye irritation, category 2 Causes serious eye irritation.
Environment:	Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Classification according to 67/548/EEC or 1999/45/EC:

EXTREMELY FLAMMABLE

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

Health: Not classified
Physical: EXTREMELY FLAMMABLE
Environment: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s):
 H222 : Extremely flammable aerosol.
 H229 : Pressurised container: May burst if heated.
 H315 : Causes skin irritation.
 H319 : Causes serious eye irritation.
 H412 : Harmful to aquatic life with long lasting effects.

Precautionary statement(s):
 P102 : Keep out of reach of children.
 P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 : Do not spray on an open flame or other ignition source.
 P251 : Do not pierce or burn, even after use.
 P280 : Wear protective gloves/protective clothing/eye protection/face protection.
 P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard information:
 Contains:
 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime
 May produce an allergic reaction.

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
dimethyl ether	115-10-6	204-065-8	30-60	F+	12	A
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	203-550-1	5-10	F,Xn	11-20-36/37-66	A
ethylbenzene	100-41-4	202-849-4	1-5	F,Xn	11-20-48/20-65	A

Productname : Zinc Primer **Creationdate :** 27.03.15 Version : 1.1
Ref.Nr.: BDS000186_3_20150327 (EN) **Replaces:** BDS000186_20130703

1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	203-539-1	1-5		10-67	A
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	202-496-6	<1	Xn	21-40-41-43	B
zinc oxide	1314-13-2	215-222-5	<1	N	50/53	B
xylene	1330-20-7	215-535-7	<12.5	Xn	10-20/21-38	A
1,2,4-trimethylbenzene	95-63-6	202-436-9	<2.5	Xn,N	10-20-36/37/38-51/53	A
mesitylene1,3,5-trimethylbenzene	108-67-8	203-604-4	<2.5	Xi,N	10-37-51/53	A
trizinc bis(orthophosphate)	7779-90-0	231-944-3	<2.5	N	50/53	

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dimethyl ether	01-2119472128-37	115-10-6	204-065-8	30-60	Flam. Gas 1, Press. Gas	H220,H280	A
4-methylpentan-2-one; isobutyl methyl ketone	01-2119473979-13	108-10-1	203-550-1	5-10	Flam. Liq. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3	H225,H332,H319,H335	A
ethylbenzene	01-2119489370-35	100-41-4	202-849-4	1-5	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1	H225,H332,H373,H304	A
1-methoxy-2-propanol; monopropylene glycol methyl ether	01-2119457435-35	107-98-2	203-539-1	1-5	Flam. Liq. 3, STOT SE 3	H226,H336	A
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	01-2119539477-28	96-29-7	202-496-6	<1	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1	H351,H312,H318,H317	B
zinc oxide		1314-13-2	215-222-5	<1	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	B
xylene	02-2119752448-30	1330-20-7	215-535-7	<12.5	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2	H226,H332,H312,H315	A
1,2,4-trimethylbenzene	ABNA	95-63-6	202-436-9	<2.5	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 2	H226,H332,H315,H319,H335,H411	A
mesitylene1,3,5-trimethylbenzene		108-67-8	203-604-4	<2.5	Flam. Liq. 3, STOT SE 3, Aquatic Chronic 2	H226,H335,H411	A
trizinc bis(orthophosphate)		7779-90-0	231-944-3	<2.5	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures**4.1. Description of first aid measures****Contact with eyes :**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

Contact with skin : Take off contaminated clothing and wash before reuse.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion : If swallowed do not induce vomiting because of risk of aspiration into the lungs.
If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Symptoms : sore throat, abdominal pain, nausea, vomiting

Skin contact : Irritating to skin
Symptoms : redness and pain

Eye contact : Irritating to eyes
Symptoms : redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible)
If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Place in appropriate container
This material and/or its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.
Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep out of reach of children.

7.3. Specific end use(s)

Paints

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method
----------------------	---------	--------

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

EU established exposure limits:			
ethylbenzene	100-41-4	TWA	100 ppm
		STEL	200 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	TWA	20 ppm
		STEL	50 ppm
mesitylene 1,3,5-trimethylbenzene	108-67-8	TWA	20 ppm
dimethyl ether	115-10-6	TWA	1000 ppm
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm
National established exposure limits, United Kingdom			
ethylbenzene	100-41-4	TWA	100 ppm
		STEL	125 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
dimethyl ether	115-10-6	TWA	400 ppm
		STEL	500 ppm
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type AX)
hands and skin :	Wear suitable protective gloves against chemicals
Recommended gloves:	Nitrile
eyes :	Wear safety goggles.
Environmental protection:	Avoid release to the environment. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance : physical state :	DME propelled liquid.
colour :	See color cap.
odour :	Characteristic odor.
pH :	Not applicable.
Boiling point/range :	Not available.
Flash point :	15 °C (Closed Cup)

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

Evaporation rate : Not available.
Explosion limits : upper limit : Not available.
lower limit : Not available.
Vapour pressure : Not available.
Relative density : 1.08 g/cm³ (@ 20°C).
Solubility in water : Insoluble in water
Auto-ignition : > 200 °C
Viscosity : Not available.

9.2. Other information

VOC: 618 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may

Productname : Zinc Primer **Creationdate :** 27.03.15 Version : 1.1
Ref.Nr.: BDS000186_3_20150327 (EN) **Replaces:** BDS000186_20130703

induce chemical pneumonia.
Skin contact : Irritating to skin
Eye contact : Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LD50 oral rat	4016 mg/kg
		LC50 inhal.rat	27596 mg/l
		LD50 derm.rabit	2000 mg/kg

SECTION 12: Ecological information**12.1. Toxicity**

Hazardous to the aquatic environment, chronic category 3
Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LC50 fish	6812 mg/l
		EC50 daphnia	23300 mg/l
zinc oxide	1314-13-2	LC50 fish	1.1 mg/l
		EC50 daphnia	0.098 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)

Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Productname : Zinc Primer
Ref.Nr.: BDS000186_3_20150327 (EN)
Creationdate : 27.03.15 Version : 1.1
Replaces: BDS000186_20130703

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.
EU-directive 99/45/EC
Regulation (EC) No 1272/2008 (CLP)
Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases:

- R10: Flammable.
- R11: Highly flammable.
- R12: Extremely flammable.
- R20: Harmful by inhalation.
- R21: Harmful in contact with skin.
- R37: Irritating to respiratory system.
- R38: Irritating to skin.
- R40: Limited evidence of a carcinogenic effect.
- R41: Risk of serious damage to eyes.
- R43: May cause sensitization by skin contact.
- R65: Harmful: may cause lung damage if swallowed.
- R66: Repeated exposure may cause skin dryness or cracking.
- R67: Vapours may cause drowsiness and dizziness.
- R20/21: Harmful by inhalation and in contact with skin.
- R36/37: Irritating to eyes and respiratory system.
- R36/37/38: Irritating to eyes, respiratory system and skin.
- R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R50/53
- R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

*Explanation hazard statements:

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H280 : Contains gas under pressure; may explode if heated.
- H304 : May be fatal if swallowed and enters airways.
- H312 : Harmful in contact with skin.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.

Productname :	Zinc Primer	Creationdate :	27.03.15 Version : 1.1
Ref.Nr.:	BDS000186_3_20150327 (EN)	Replaces:	BDS000186_20130703

H336 : May cause drowsiness or dizziness.

H351 : Suspected of causing cancer .

H373 : May cause damage to organs through prolonged or repeated exposure

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

H411 : Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.