



ASSEMBLY PASTE FG **FOOD PROCESSING SAFE® PASTE ASSISTS ASSEMBLY** **OF COMPONENTS**

ASSEMBLY PASTE FG is a tenacious high solids paste formulated specifically for use in the food industry. Used as a start-up lubricant, the paste reduces wear to moving components during the running in period. The active compound provides instant lubrication to bearings and sliding surfaces.

FEATURES

- NSF H1 registered (N° 139900) for use in food industry
- Low friction coefficient provides protection during running in, prolonging component life
- Provides protection against scuffing during assembly
- Prevents seizure of threaded components enabling easy and quick dismantling
- Dismantled threaded components can be reused
- Compatible with most grease types
- Prevents galling and metal-on-metal damage
- Allows moving components to be run at full operating speed sooner without the risk of friction build-up.
- Effective from -30°C to +150°C as a lubricant and up to +1100°C as an anti-seize

DIRECTIONS

Aerosol:

- When using the aerosol, shake well before application.
- Spray uniformly with short intervals. When possible move the fitting parts gently while spraying.

TECHNICAL DATA

| | | |
|------------------------------|---|---------------------------|
| NSF Registered, Category | : | H1 (N° 139900) |
| Appearance | : | White Paste |
| Carrier | : | Synthetic lubricating oil |
| Specific Gravity (@ 20°C) | : | 0.67 (aerosol) |
| Water washout (@ 38°C) | : | <1% (ASTM D1264) |
| Dynamic corrosion resistance | : | 0:0 (EMCOR) (IP220) |
| Solubility In Water | : | Insoluble |
| Packaging | : | 400 ml Aerosol |

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersil.com

E-mail: sales.uk@crcind.com