


Technical Data



FLT CHAINLUBE **MECHANICAL HANDLING CHAIN LUBRICANT**



FLT CHAINLUBE is a chain lubricant specifically formulated for use on chains, drives, and tail-lifts in mechanical handling applications. Excellent penetration and tenacity ensures long lasting lubrication. Resists water wash-off. Protects against corrosion.

TECHNICAL DATA

| | | |
|--------------------------|---|--|
| Appearance | : | Brown foaming lubricant. |
| Odour | : | Solvent. |
| Specifications/Approvals | : | Lansing Bagnall Approved |
| SG @ 20°C (aerosol) | : | 0.69 |
| Pressure @ 20°C | : | 3.7 bar. |
| Discharge rate @ 20°C | : | 1.2 g/s |
| Temperature range | : | Up to 200°C continuously. Between 200 and 300°C intermittently, subject to tests on intended application prior to general use. |
| Solubility | : | Insoluble in water, soluble in hydrocarbon solvents. |
| Compatibility | : | Safe to use on running chains |
| Flammability | : | Classified as extremely flammable under current EU regulations. |
| Flashpoint | : | Not applicable in sealed aerosol. |
| Packaging | : | 500 ml aerosol (12 per carton). |

STORAGE

The product may be stored at normal ambient temperatures and has a shelf

life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Ltd, Wylde Road, Bridgwater, Somerset, TA6 4DD, UK.

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersil.com

E-mail: sales.uk@crcind.com