

DOCUMENT GROUP: DATE: REVISION DATE: CHEMICAL/REPAIR/SYSTEMS 1ST NOVEMBER 2017 1ST NOVEMBER 2018

VERSION REF: VERSION NO: SUPERSEDES DATE: 11635/BC405EPC 2.00 1ST NOVEMBER 2016

MATERIAL SAFETY DATA SHEET BC 405 EPC EPOXY PROTECTIVE COATING

SUPPLIER:

BRADECHEM LIMITED, UNIT 1 THE BUSINESS VENUE, GRANDHOLM, ABERDEEN,

AB22 8AA, UNITED KINGDOM TELEPHONE NUMBER: +44 (0) 1224 822 227

EMAIL: <u>SALES@BRADECHEM.COM</u>

EMERGENCY TELEHONE NUMBER: +44 (0) 1224 822 227

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

TRANSPORTATION INFORMATION

ACTIVATOR	BASE
UN number: UN2735	UN number: UN3082
UN proper shipping name	UN proper shipping name
Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.	Shipping name: ENVIRONMENTALLY HAZARDOUS
(4-TERT-BUTYLPHENOL)	SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A-
Transport class: 8	(EPICHLORHYDRIN) {REACTION PRODUCT})
Packing group	Transport class: 9
Packing group:	Packing group
Environmental hazards	Packing group: III
Environmentally hazardous: No Marine pollutant: No	Environmentally hazardous: Yes Marine pollutant:
Special precautions for user	Yes
Special precautions: No special precautions.	Special precautions for user
Tunnel code: E	Tunnel code: E
Transport category: 3	Transport category: 3



DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BC 405 EPC EPOXY PROTECTIVE COATING ACTIVATOR

- 1.2. Relevant identified uses of the substance or mixture and uses advised against
- 1.3. Details of the supplier of the safety data sheet

Company name:

1.3 Details of the supplier of the safety data sheet

Bradechem Limited, Unit 1 The Business Venue, Grandholm, Aberdeen, AB22 8AA

Tel: +44 (0) 1224 822 227 Email: sales@bradechem.com

1.4 Emergency telephone number

+44 (0) 1224 822 227 (9am to 5pm)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 3: H412; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1A: H317

Most important adverse effects: Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed. H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction. H361f: Suspected of damaging fertility.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazardGHS09: Environmental







Precautionary statements: P102: Keep out of reach of children.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe vapours.

P273: Avoid release to the environment.



P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	PBT/WEL	CLP CLASSIFICATION	PERCENT
202-859-9	100-51-6	-	Acute Tox. 4: H332;	10-30%
			Acute Tox. 4: H302	
4-TERT-BUTYL	PHENOL			
202-679-0	98-54-4	-	Repr. 2: H361f; Skin	10-30%
			Irrit. 2: H315; Eye	
			Dam. 1: H318	
M-PHENYLENE	BIS(METHYLAMINE)			
040,000 5	4477.55.0		101: 0 45 11044	140,000/
216-032-5	1477-55-0	-	Skin Corr. 1B: H314;	10-30%
			Acute Tox. 4:	
			H302; Skin Sens. 1:	
			H317; Aquatic Chronic 3: H412;	
			Acute Tox. 4: H332	
247-062-2	25513-64-8	-	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412;	1-10%
			Acute Tox. 4: H312	
3-AMINOMETH	YL-3,5,5-TRIMETHYLCY(CLOHEXYLAMINE		
220-666-8	2588-13-2	T -	Acute Tox. 4: H312;	1-10%
220 000 0	2300-13-2		Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1:	1.576
			H317; Aquatic	

Chronic 3: H412



4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	-	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	1-10%
-----------	---------	---	---	-------

3-AMINOPROPYLDIMETHYLAMINE

203-680-9	109-55-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1:	1-10%
			H317	

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

202-013-9	90-72-2	-	Acute Tox. 4: H302;	1-10%
			Eye Irrit. 2: H319;	
			Skin Irrit. 2: H315	

PHENOL, STYROLISED

262-975-0	61788-44-1	-	Skin Irrit. 2: H315;	1-10%
			Skin Sens. 1: H317;	
			Aquatic Chronic 2:	
			H411	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.



Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging...

7.3. Specific end use(s)

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters Hazardous ingredients:

4,4'-ISOPROPYLIDENEDIPHENOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min STEL
UK	5 mg/m3	5 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls



Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of

emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Amber Odour: Ammoniacal Solubility in water: Insoluble Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >100 Autoflammability°C: 380 Relative density: 1.0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid Conditions to avoid: Heat. 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360`	mg/kg
ORL	RAT	LD50	1230	mg/kg

M-PHENYLENEBIS(METHYLAMINE)

DERMAL	RAT	LD50	3100	mg/kg
ORAL	RAT	LD50	930	mg/kg

TRIMETHYLHEXANE-1,6-DIAMINE



DARMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	930	mg/kg

Bradechem ISO9001 Registered Firm

4,4'-ISOPROPYLIDENEDIPHENOL

ORL	MUS	LD50	2400	mg/kg
SKN	RBT	LD50	600	mg/kg

3-AMINOPROPYLDIMETHYLAMINE

ORL	RAT	LD50	1870	mg/kg
SKN	RBT	LD50	600	mg/kg

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

1	ORL	RAT	LD50	1200	mg/kg
	SKN	RAT	LD50	1280	ma/ka

PHENOL, STYROLISED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac.tox.4)	ING	Hazardous: calculated
Skin corrosion/ irritation	DRM	Hazardous: calculated
Serious eye damage/ irritation	OPT	Hazardous: calculated
Respiratory Toxicity	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

TRIMETHYLHEXANE-1,6-DIAMINE

FISH 96H LC50 174 mg/l



PHENOL, STYROLISED

DAPHNIA	48H EC50	1-10	mg/l
FISH	96H LC50	14.8	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(4-TERT-BUTYLPHENOL)

14.3. Transport hazard class(es)

Transport class: 8 14.4. Packing group Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable. 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the

mixture

by the supplier.



Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

- H302: Harmful if swallowed.
- H312: Harmful in contact with skin.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H361f: Suspected of damaging fertility.
- H411: Toxic to aquatic life with long lasting effects.
- H412: Harmful to aquatic life with long lasting effects.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

Section 1: Identification of the substance/mixture and of the company/undertaking



1.1. Product identifier

Product name: BC 405 EPC EPOXY PROTECTIVE COATING BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Bradechem Limited, Unit 1 The Business Venue, Grandholm, Aberdeen, AB22 8AA

Tel: +44 (0) 1224 822 227 Email: sales@bradechem.com

1.4 Emergency telephone number

+44 (0) 1224 822 227 (9am to 5pm)

Section 2: Hazards identification

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43; N: R51/53

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -:

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements:

Hazard statements: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Precautionary statements: P102: Keep out of reach of children.

P273: Avoid release to the environment. P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP: Hazard symbols: Irritant. Dangerous for the environment.





Risk phrases: R36/38: Irritating to eyes and skin. R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin. S29: Do not empty into drains. S37: Wear suitable gloves. S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP classification	CLP Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

BISPHENOL F TYPE EPOXY RESIN

500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	--	--------

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

271-846-8	68609-97-2	Xi: R38; Sens.: R43	Skin Irrit. 2: H315; Skin Sens. 1: H317	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.



Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of

water to drink immediately. Consult a doctor.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. **Eye protection:** Safety glasses.

Skin protection: Impermeable protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.



Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Various

Odour: Barely perceptible odour Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >150

Relative density: 1.75g/cc 9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Amines. Alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Teat	Value	Units
ORAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RAT	LD50	>20	mg/kg

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

ORL	RAT	LD50	17100	ma/ka

Relevant effects for mixture:



Effect	Route	Basis	
Irritation	OPT DRM	Hazardous; calculated	
Sensitisation	DRM	Hazardous; calculated	

Bradechem ISO9001 Registered Firm

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96h lc50	2	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Mixed material, once fully cured, can be disposed as solid waste.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. **NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A-

(EPICHLORHYDRIN) {REACTION PRODUCT})

14.3. Transport hazard class(es)

Transport class: 9
14.4. Packing group
Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: E Transport category: 3



Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects. R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.