#### Regulation EC No 1907/2006 Art.31

GEAR OIL LO 220 FG Creationdate: 25.08.15 Version: 1.0 Productname: Ref.Nr.: UDS000520 3 20150825 (EN) Replaces: UDS000520 20120625

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **GEAR OIL LO 220 FG**

Bulk

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

#### 1.3. Details of the supplier of the safety data sheet

**CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom** 

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

#### 1.4. Emergency telephone number

(+44)(0)1278 72 7200

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Physical: Not classified Health: Not classified

**Environment:** Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

#### Classification according to 67/548/EEC or 1999/45/EC:

Health: Not classified Physical: Not classified

**Environment:** R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Other hazards: Not classified



## Regulation EC No 1907/2006 Art.31

Productname: **GEAR OIL LO 220 FG** 

Ref.Nr.: UDS000520 3 20150825 (EN) Creationdate: Replaces:

25.08.15 Version: 1.0 UDS000520 20120625

#### 2.2. Label elements

## Labelling according to Regulation (EC) No 1272/2008

Hazard statement(s): H412: Harmful to aquatic life with long lasting effects.

P273: Avoid release to the environment.

P501-2: Dispose of contents/container to an authorised waste collection point.

#### 2.3. Other hazards

None

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable.

#### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
2,6-di-tert-butyl-p-cresol	128-37-0	204-881-4	0-2.5	N	50/53	В
Amines, C11-14-branched alkyl, monohexyl and dihexyl phosphates	80939-62-4	279-632-6	0-2.5	Xi,N	36/38-51/53	
Explanation notes						
B : substance with national established workplace exposure limit						

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes					
2,6-di-tert-butyl-p-cresol		128-37-0	204- 881-4	0-2.5	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	В					
Amines, C11-14-branched alkyl, monohexyl and dihexyl phosphates		80939- 62-4	279- 632-6	0-2.5	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2	H315,H319,H411						
Explanation notes												
B : substance with national established workplace exposure limit												

<sup>(\*</sup> Explanation phrases : see chapter 16)

## 4.1. Description of first aid measures

SECTION 4: First aid measures

If substance has got into eyes, immediately wash out with plenty of water for Contact with eyes:

several minutes

Seek medical attention if irritation persists

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention if ill effects occur

Ingestion: If swallowed do not induce vomiting



## Regulation EC No 1907/2006 Art.31

 Productname :
 GEAR OIL LO 220 FG
 Creationdate :
 25.08.15 Version : 1.0

 Ref.Nr.:
 UDS000520\_3\_20150825 (EN)
 Replaces:
 UDS000520\_20120625

Seek medical advice

#### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation:** Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

**Ingestion:** May cause gastrointestinal disturbances

Symptoms: sore throat, abdominal pain, nausea, vomiting

**Skin contact :** Mildly irritating to skin

Symptoms: redness and pain

**Eye contact :** Mildly irritating to eyes

Symptoms: redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice:** If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

# SECTION 5: Firefighting measures

## 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Forms hazardous decomposition products CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation

Wear suitable protective clothing including eye/face protection.

## 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

#### 6.3. Methods and material for containment and cleaning up



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

#### Regulation EC No 1907/2006 Art.31

GEAR OIL LO 220 FG Productname:

Ref.Nr.: UDS000520 3 20150825 (EN)

Creationdate: Replaces:

25.08.15 Version: 1.0 UDS000520 20120625

Absorb spillage in suitable inert material

#### 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Use only in well ventilated areas Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated place Keep out of reach of children.

#### 7.3. Specific end use(s)

Lubricants

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### **Exposure limits:**

No information available

# 8.2. Exposure controls

**Control procedures:** Ensure adequate ventilation

Take precautions to avoid contact with skin and eyes when handling the Personal protection:

product.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

hands and skin: Wear suitable protective gloves against chemicals

eyes: Wear safety goggles.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Apperance : physical state : Liquid.



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

## Regulation EC No 1907/2006 Art.31

Creationdate: Productname: **GEAR OIL LO 220 FG** 25.08.15 Version: 1.0 Ref.Nr.: UDS000520 3 20150825 (EN) Replaces: UDS000520 20120625

220 cSt @ 40°C

Colorless. colour: odour: Odorless. Not applicable. pH: Boiling point/range: > 300 °C > 245 °C Flash point: Evaporation rate: Not available. **Explosion limits : upper limit :** Not available. lower limit: Not available. Vapour pressure : Not available. 0.870 (@ 20°C). Relative density: Solubility in water: Insoluble in water Auto-ignition: > 325 °C

#### 9.2. Other information

Viscosity:

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

## 10.2. Chemical stability

Stable

## 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

## 10.4. Conditions to avoid

Avoid overheating

#### 10.5. Incompatible materials

Strong oxidising agent

#### 10.6. Hazardous decomposition products

CO,CO2

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Information on likely routes of exposure:



#### Regulation EC No 1907/2006 Art.31

GEAR OIL LO 220 FG Creationdate: 25.08.15 Version: 1.0 Productname: Ref.Nr.: UDS000520 3 20150825 (EN) Replaces: UDS000520 20120625

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: May cause gastrointestinal disturbances

Skin contact: May cause irritation. Eye contact : May cause irritation.

#### Toxicological data:

No information available

# SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

#### Ecotoxicological data:

No information available

## 12.2. Persistence and degradability

No information available

#### 12.3. Bioaccumulative potential

No information available

#### 12.4. Mobility in soil

Insoluble in water

# 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

No information available

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

#### Regulation EC No 1907/2006 Art.31

GEAR OIL LO 220 FG Creationdate: 25.08.15 Version: 1.0 Productname: Ref.Nr.: UDS000520 3 20150825 (EN) Replaces: UDS000520 20120625

waste collection point.

Contaminated packaging: Disposal should be in accordance with local, state or national legislation

# SECTION 14: Transport information

#### 14.1. UN number

**UN-number:** Not classified as hazardous for transport

#### 14.2. UN proper shipping name

Proper shipping name: Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable. Class: ADR/RID - Classification code: Not applicable.

## 14.4. Packing group

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally No

hazardous:

IMDG - Marine pollutant: No

IATA/ICAO - Environmentally

hazardous:

No

#### 14.6. Special precautions for user

IMDG - Ems: Not applicable.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

EU-directive 99/45/EC

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

#### 15.2. Chemical safety assessment



7/8

## **CRC Industries UK Limited**

#### Regulation EC No 1907/2006 Art.31

Productname: GEAR OIL LO 220 FG Creationdate: 25.08.15 Version: 1.0 Ref.Nr.: Replaces: UDS000520 3 20150825 (EN) UDS000520 20120625

No information available

# SECTION 16: Other information

\*Explanation risk-phrases: R36/38: Irritating to eyes and skin.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects

in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

\*Explanation hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation. H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

