Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces: 08.01.15 Version : 1.0 UDS000375_20120516

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MOULD CLEANER

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Health: Skin sensitization, category 1

May cause an allergic skin reaction.

Environment: Hazardous to the aquatic environment, chronic category 2

Toxic to aquatic life with long lasting effects.

Classification according to 67/548/EEC or 1999/45/EC:

EXTREMELY FLAMMABLE

Xi: IRRITANT



Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces:

08.01.15 Version : 1.0 UDS000375 20120516

N: DANGEROUS FOR THE ENVIRONMENT

Health: R43: May cause sensitization by skin contact.

Physical: R12: Extremely flammable. EXTREMELY FLAMMABLE

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

2.2. Label elements

Environment:

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:

Orange, sweet, extract

Hazard pictogram(s):







Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated. H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statement(s): P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280 : Wear protective gloves/protective clothing/eye protection/face

protection.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	•	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990-9	30-60	F+	12	K,G



Regulation EC No 1907/2006 Art.31

Productname:

MOULD CLEANER

Creationdate:

08.01.15 Version: 1.0

Ref.Nr.:

UDS000375_3_20150108 (EN)

Replaces:

UDS000375_20120516

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	(926-141- 6)	30-60	Xn	65-66	В	
Orange, sweet, extract		232-433-8	1-5	Xn,N	10-38-43-50/53- 65		
Explanation notes							
B : substance with national established workplace exposure limit							
G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006							

Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	-	68512- 91-4	270- 990-9	30- 60	Press. Gas, Flam. Gas 1	H280,H220	K,G
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01- 2119456620- 43	-	(926- 141-6)	30- 60	Asp. Tox. 1	H304	В
Orange, sweet, extract	01- 2119493353- 35	8028- 48-6	232- 433-8	1-5	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1	H226,H315,H317,H304,H400,H410	_

Explanation notes

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

SECTION 4: First aid measures

4.1. Description of first aid measures

If substance has got into eyes, immediately wash out with plenty of water Seek medical advice
Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water Seek medical advice
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms: sore throat, abdominal pain, nausea, vomiting
Skin contact :	Irritating to skin May cause sensitisation by skin contact.



^{(*} Explanation phrases : see chapter 16)

Regulation EC No 1907/2006 Art.31

Productname:

Ref.Nr.:

MOULD CLEANER

UDS000375_3_20150108 (EN)

Creationdate : Replaces:

08.01.15 Version : 1.0 UDS000375_20120516

Symptoms: redness and pain

Eye contact : May cause irritation.

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO.CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation

Wear protective gloves/protective clothing/eye protection/face protection.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage



Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces: 08.01.15 Version : 1.0 UDS000375_20120516

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Do not get in eyes, on skin, or on clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Heavy duty

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

No information available

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

hands and skin: Wear suitable protective gloves against chemicals

Recommended gloves: Nitrile

eyes: Wear safety goggles.

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces:

08.01.15 Version : 1.0 UDS000375_20120516

(for aerosols data for the product without propellant)

Apperance : physical state : Propane/butane propelled liquid.

colour :Colorless.odour :Citrus.

pH: Not applicable.

Boiling point/range : 173 °C **Flash point :** 46 °C

Evaporation rate : Not available.

Explosion limits : upper limit : 9.4 % lower limit : 0.6 %

Vapour pressure: Not available.

Relative density: 0.805 g/cm3 (@ 20°C).

Solubility in water : Insoluble in water

Auto-ignition :225 °CViscosity :Not available.

9.2. Other information

VOC: 656 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information



Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces:

08.01.15 Version : 1.0 UDS000375_20120516

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents may

induce chemical pneumonia.

Skin contact : May cause sensitisation by skin contact.

Irritating to skin

Eye contact : May cause irritation.

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	LD50 oral rat	> 5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment



Regulation EC No 1907/2006 Art.31

Productname:

MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces: 08.01.15 Version : 1.0 UDS000375_20120516

No information available

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS (Orange sweet ext.)

Yes

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally Yes

hazardous:

IMDG - Marine pollutant: Marine pollutant

IATA/ICAO - Environmentally

hazardous:

14.6. Special precautions for user

 ADR/RID - Tunnelcode:
 (D)

 IMDG - Ems:
 F-D, S-U

 IATA/ICAO - PAX:
 203



Regulation EC No 1907/2006 Art.31

Productname: MOULD CLEANER

Ref.Nr.: UDS000375_3_20150108 (EN)

Creationdate : Replaces:

08.01.15 Version : 1.0 UDS000375 20120516

IATA/ICAO - CAO

203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases: R10: Flammable.

R12: Extremely flammable. R38: Irritating to skin.

R43: May cause sensitization by skin contact. R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects

in the aquatic environment.

*Explanation hazard statements: H220: Extremely flammable gas.

H226: Flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

