

Bradechem Ltd

Registered Office: Unit 1 The Business Venue Grandholm Aberdeen AB22 8AA

Tel: +44(0)1224 822227 E-mail sales@bradechem.com

February 2006

TECHNICAL DATA SHEET

BRADECHEM SILICONE GREASE.

DESCRIPTION:

Bradechem Silicone Grease is compounded from dimethyl polysiloxane fluid, the product has a broad temperature range and is chemically inert, being resistant to; water (hot, cold, steam & brine), lubricating oils, most hydrocarbons & solvents, natural gas, refinery gases & condensate and many acidic solutions.

APPLICATIONS:

Bradechem Silicone Grease has been designed for the lubrication of; cylinder slides, taps, valves & stopcocks (where the presence of chemicals & solvents mean that conventional products can not be used).

The product is suitable for use as a damping compound – both under conditions of high pressures and elevated temperature.

The excellent dielectric properties of the grease mean that the product can be used with high voltage electrical systems for lubricating non-conducting contacts, preventing corona discharge and for preventing flashover on high voltage anodes.

TYPICAL PHYSICAL CHARACTERISTICS:

Appearance	Smooth Gel.
Colour	White Semi-Translucent.
NLGI Classification	3
Odour	Very Slight
Temperature Range	-40°C to over +200°C
Drop Point	None
Thickening Agent	Inorganic Thickener System
Flash Point	>315°C

PACKAGING:

400g Cartridges (Boxes of 36), 500g Tins (Boxes of 6), 4.5 Kilo Tins, 12.5 Kilo Kegs, 50 Kilo Kegs, 180 Kilo Barrels.

(Other pack sizes may be available by request).